



**HAL**  
open science

## Memory Manipulations in Extended Reality

Elise Bonnail, Eric Lecolinet, Wen-Jie Tseng, Mark McGill, Samuel Huron, Jan  
Gugenheimer

► **To cite this version:**

Elise Bonnail, Eric Lecolinet, Wen-Jie Tseng, Mark McGill, Samuel Huron, et al.. Memory Manipulations in Extended Reality. In Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems (CHI '23), Apr 2023, Hamburg, Germany. 10.1145/3544548.3580988 . hal-04058016

**HAL Id: hal-04058016**

**<https://imt.hal.science/hal-04058016v1>**

Submitted on 4 Apr 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Memory Manipulations in Extended Reality

Elise Bonnail

LTCI, INFRES, Telecom Paris, IP Paris  
Palaiseau, France  
elise.bonnail@telecom-paris.fr

Wen-Jie Tseng

LTCI, INFRES, Telecom Paris, IP Paris  
Palaiseau, France  
wen-jie.tseng@telecom-paris.fr

Mark McGill

University of Glasgow  
Glasgow, Scotland, UK  
mark.mcgill@glasgow.ac.uk

Eric Lecolinet

LTCI, INFRES, Telecom Paris, IP Paris  
Palaiseau, France  
eric.lecolinet@telecom-paris.fr

Samuel Huron

CNRS i3 (UMR 9217), SES, Telecom  
Paris, IP Paris  
Palaiseau, France  
samuel.huron@telecom-paris.fr

Jan Gugenheimer

TU Darmstadt  
Darmstadt, Germany  
LTCI, INFRES, Telecom Paris, IP Paris  
Palaiseau, France  
jan.gugenheimer@tu-darmstadt.de

## ABSTRACT

Human memory has notable limitations (e.g., forgetting) which have necessitated a variety of memory aids (e.g., calendars). As we grow closer to mass adoption of everyday Extended Reality (XR), which is frequently leveraging perceptual limitations (e.g., redirected walking), it becomes pertinent to consider how XR could leverage memory limitations (forgetting, distorting, persistence) to induce memory manipulations. As memories highly impact our self-perception, social interactions, and behaviors, there is a pressing need to understand XR Memory Manipulations (XRMMs). We ran three speculative design workshops (n=12), with XR and memory researchers creating 48 XRMM scenarios. Through thematic analysis, we define XRMMs, present a framework of their core components and reveal three classes (*at encoding, pre-retrieval, at retrieval*). Each class differs in terms of technology (AR, VR) and impact on memory (influencing quality of memories, inducing forgetting, distorting memories). We raise ethical concerns and discuss opportunities of perceptual and memory manipulations in XR.

## CCS CONCEPTS

• **Human-centered computing** → **Virtual reality; Mixed / augmented reality.**

## KEYWORDS

XR Memory Manipulations, Perceptual Manipulations, Speculative Design, Extended Reality, Virtual Reality, Augmented Reality

### ACM Reference Format:

Elise Bonnail, Wen-Jie Tseng, Mark McGill, Eric Lecolinet, Samuel Huron, and Jan Gugenheimer. 2023. Memory Manipulations in Extended Reality. In *Proceedings of the 2023 CHI Conference on Human Factors in Computing Systems (CHI '23)*, April 23–28, 2023, Hamburg, Germany. ACM, New York, NY, USA, 20 pages. <https://doi.org/10.1145/3544548.3580988>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

*CHI '23, April 23–28, 2023, Hamburg, Germany*

© 2023 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-1-4503-9421-5/23/04...\$15.00

<https://doi.org/10.1145/3544548.3580988>

## 1 INTRODUCTION

Human memory is known to have a set of limitations. Long-term memories can be forgotten (when they are inaccessible), distorted (when they differ from the original perception), or persistent (when they cannot be forgotten) [106]. As our memories influence our thoughts and behaviors, memory limitations can have a significant detriment to our lives and social relationships. Addressing these limitations is what has given rise to the continual development of new archival mediums (writing, pictures, video) and memory aids (from post-it notes to AI assistants). Seeing the recent rise of Extended Reality (XR) consumer technology (e.g., Meta, Apple, Microsoft), we argue it has the potential to become a ubiquitous technology, able to augment and impact the human intellect, and in particular memory [39]. One example would be the ability to revisit past memories in Virtual Reality (VR). Using immersive 3D reconstructions of past events creates a sense of presence and embodiment, which enhances episodic memory performance [77, 118] and offers a more attractive way to reminisce [137].

However, while memory limitations can be compensated, they can also be exploited to manipulate memory. Due to the suggestibility of memory, altering a picture can distort memories related to it and lead to the creation of false memories [86, 98, 134]. XR being a richer media than a regular 2D picture, it could facilitate the creation of false memories [109], and more generally facilitate memory manipulations. In addition, XR has demonstrated its ability to take advantage of human perceptual limitations to manipulate users, which we refer to as perceptual manipulations. Much research is focused on Virtual-Physical Perceptual Manipulations (VPPMs) [126], which exploit the limitations of human perception in order to effect changes in users' physical movements (e.g., redirected walking [123], haptic retargeting [5]). Similar to perception, memory has limitations (forgetting, distorting, persistence [106]) that could be exploited in XR to induce memory manipulations, which we refer to as *XR Memory Manipulations* (XRMMs). Although VPPMs can enhance users' XR experience (e.g., by enabling a longer virtual walking experience despite limited physical space [123]), these manipulations are generally imperceptible and the intent behind the use of VPPMs is open to abuse [19, 126]. While these perceptual manipulations have an immediate impact on users' physical actions, memory manipulations could be more invasive and have longer-term impact on users' self-perception, social interactions,

and behaviors (through the three autobiographical memory functions [14]). Therefore, it is crucial that we understand the extent to which our memory can be manipulated with XR, and how this technology can uniquely contribute to or amplify these manipulations.

In this paper, we strive to understand what types of memory manipulations are possible in XR, and how the technology works as an enabler or amplifier in these manipulations. To broadly explore the scope of XRMMs, we ran three speculative design workshops, each with two XR researchers and two cognitive psychology researchers having strong knowledge about memory ( $n=12$ ). We used speculative design methods to envision future scenarios while still grounding the workshop in our current understanding of memory processes and XR capabilities. During these workshops, experts were asked to individually generate scenarios of XRMMs, resulting in 48 XRMM scenarios. The scenarios focused on specific questions: who would use the application, how the manipulation would work and why would it be used, grounded on which cognitive process and XR specific features. Consecutively, experts selected their most promising scenarios that were additionally discussed in more depth to assess, from both technical and cognitive point of views, if they are likely to be implemented in the future, and to discuss their outcomes (22 discussed XRMM scenarios). Three authors coded the data and used thematic analysis in seven sessions (each four hours) to uncover underlying themes and mechanisms used.

From this analysis, we define XR Memory Manipulations (XRMMs) as *perceptual manipulations grounded in memory limitations with the intention to impact memories, leading to long-term effects on users, through the self, social and directive functions of autobiographic memory*. From the data, we discovered five core components that characterize memory manipulations (*context, memory mechanism, implementation, memory functions, and final goal*). We present these as the framework of XRMMs. Additionally, we found three classes of XRMMs that differ in terms of technology and outcomes: 1) manipulations occurring *at encoding* (i.e., simultaneously as the original perception of the event), which aim at *influencing the quality of memory encoding* and predominantly *rely on Augmented Reality (AR) technologies* (e.g., steering user attention with AR to make the encoding of memories stronger); 2) manipulations occurring *at retrieval* (i.e., when past events are digitally revisited), which aim at *distorting the perception of a past event* and predominantly *rely on immersive reconstruction of scenes in Virtual Reality (VR)* (e.g., altering a recording of prior event to overwrite the original memory); 3) manipulations occurring *pre-retrieval* (i.e., just before the memory is remembered), which aim at *inducing forgetting* (e.g., hiding elements in AR to help someone to forget something). Most of the scenarios take advantage of features unique to XR, which enable new types of memory manipulations. Although some XRMM scenarios do not fully depend on XR to be delivered and are adapted from already existing techniques using more traditional media (e.g., pictures), we present a discussion about how XR-specific features (e.g., the capacity to fully immerse users in a virtual environment) could amplify the effect of memory manipulations. While several scenarios have a positive intent (13 positive, 9 negative discussed scenarios), some of them could, intentionally or not, represent harms that need to be addressed. During the discussion, most experts raised ethical concerns and were worried about future abuse.

We present a final discussion around the potential benefits XRMMs could generate, their potential dangers, and what role our community of HCI researchers is playing in the pursuit of researching and improving perceptual manipulations in XR. We argue that XRMMs are a new type of perceptual manipulation in XR, whose focus is not on impacting immediate actions but on impacting users' on the long-term, through the self, social and directive functions of autobiographical memory.

This work has two main contributions: 1) The definition of XRMMs and a framework presenting the core components that characterize these manipulations; 2) The classification of three classes of memory manipulation in XR and insights about their unique technical characteristics and outcomes (manipulations *at encoding* influencing the quality of memories with AR, manipulations *at retrieval* distorting memories with VR, manipulations *pre-retrieval* inducing forgetting), grounded in ongoing cognitive psychology and XR research.

## 2 BACKGROUND

In this section we present a necessary background about human memory (processes, impacts and limitations) grounded in cognitive psychology research, and our premise of ubiquitous XR technology. The knowledge we present in this section was also explained as an introduction to our workshop, to bridge the gap between experts from both fields.

### 2.1 Human Memory

Memory refers to the cognitive process of remembering information. It is a broad term, as there are many different types of memory, each with specific capacities and functions. The model proposed by Shiffrin and Atkinson differentiates sensory and short-term memory from long-term memory [112]. In this paper, we focus on long-term memory, which stores information that have been processed thoroughly, as it is the type of memory for which we use technology support more frequently (section 3.1). The formation of long-term memories occurs in three stages [82, 112]: *encoding* (acquiring of new information captured by the senses), *storage* (maintaining and retaining information over time), and *retrieval* (recalling or recognizing previously stored information).

**2.1.1 Autobiographical Memory Functions.** In this work, we particularly focus on Autobiographical Memories (AM), which includes recollected memories of personal experiences and general knowledge of the self [40], as it defines and impacts many aspects of an individual's life. Bluck and Alea [14] name three AM functions: 1) the *self function*, which maintains self coherence over time (e.g., personality, personal beliefs); 2) the *social function*, which helps developing and maintaining connections with others (e.g., remembering conversations with friends or being able to tell an anecdote); 3) the *directive function*, which guides present and future thoughts and behaviors (e.g., deciding to buy something based on previous experience). Unlike other types of perceptual manipulations (e.g., VPPMs [126]) which have a brief and immediate impact on users, memory manipulations could have a longitudinal and long-term impact on users, through the three AM functions (e.g., impacting their self-perception, social interactions and behaviors).

Memory limitation		Description	Example
<b>Forgetting:</b> When we fail to bring to mind an information	<b>Transience</b>	Decreasing accessibility of memory over time	Forgetting what exactly happened 10 years ago
	<b>Absent-mindedness</b>	Inattentive processing contributes to weak memories	Forgetting location of keys or glasses
	<b>Blocking</b>	Temporary inaccessibility of memory	Temporarily forgetting a word
<b>Distorting:</b> When a memory differs from the original perception	<b>Misattribution</b>	Attributing a memory to the wrong source	Confusion between imagined and real events
	<b>Suggestibility</b>	New information can be implanted to a memory	Inducing false memories through leading questions
	<b>Bias</b>	Influence of current knowledge and beliefs on memories	Current mood influences perception of the past
<b>Persistence:</b> When a memory cannot be forgotten		Inability to forget unwanted memories	Flashbacks of traumatic memories

**Table 1: Seven sins of memory presented by Daniel Schacter [106]. We refer to them as memory limitations**

**2.1.2 Memory Limitations.** Memory plays a ubiquitous role in our lives, but many errors can occur at each stage of the memory process. Schacter et al. classified memory limitations into seven basic “sins”, that can be separated into three types: *forgetting*, *distorting*, and *persistence* (Table 1). We give more explanations about these memory limitations when discussing the grounding of XRMM classes (sections 6, 7, 8).

We argue that these memory limitations are the equivalent of perceptual thresholds leveraged in VPPMs. They are limitations in the cognitive system which applications could leverage or overcome to achieve a desired outcome around the user.

## 2.2 Extended Reality (XR)

Our research works under the premise that future XR technologies will become ubiquitous (similar to smartphones nowadays), and that users will engage with it on a daily basis, in every life context (mobile, stationary [48, 49]). We envision a technology that is not focusing on either AR or VR but presents one device (whatever the shape might be) that is capable to function across the whole spectrum of the Milgram Continuum [84]. This would provide the user the ability to augment the real world (AR), but also the ability to be immersed in a fully virtual scene when necessary (VR). We refer to this concept as ubiquitous XR.

## 3 RELATED WORK

### 3.1 Memory Aids

HCI research about memory has mainly been focused on memory aids, aiming to compensate memory failures, to improve performance on everyday tasks requiring memory [58]. Charness et al. distinguish two types of memory supportive technology: internal memory aids, that support the memory processes, and external memory aids, that substitute and offload memory processes [21].

However, offloading memory can also impair memory and expose users to manipulations [38, 98].

**3.1.1 Internal Memory Aids.** Internal memory aids are techniques that support the cognitive process of memorizing, to make it more efficient [21]. One example is the method of Loci, which helps to memorize information by mentally associating them to familiar places [120]. HCI research has explored how this memorization technique can be done using visual displays [30, 35, 71], and how mnemonics can help users remembering information such as passwords [1, 15, 20, 35, 62]. The method of Loci has been adapted to XR using virtual memory palaces [72, 101, 131, 138], as immersion can aid recall [68]. In this paper, we explore in a broader way how XR specific functionalities could be leveraged to influence cognitive processes (e.g., to support or impair memorization).

**3.1.2 External Memory Aids.** External memory aids aim to substitute memory and offload the cognitive process of memorizing (using external storage to offload the quantity of memories stored in mind) [21]. These tools can substitute prospective memory (memory of actions to do), to ensure that we remember things we intend to do in the future (e.g., using calendar to remember to attend an appointment). New technologies (e.g., smartphones) provide effective reminder tools (e.g., Google calendar [80]) [18, 58, 59, 113]. External memory aids can also substitute retrospective memory (memory of past events), to increase the amount of past events that can be recalled (e.g., by storing pictures in a computer) [18, 58]. With the ubiquity of smartphones and data storage becoming cheaper, people can record anything at any time, a practice called lifelogging [51, 52]. These technologies support reminiscence and reflection [26, 57], which improves well-being [16, 57]. The rich contextual information of images facilitates autobiographical recollection [9, 110]. Instead of viewing recordings on a flat screen, these could be stored as 3D scenes that one could revisit with a VR HMD. This idea is started

to be explored by companies and artists [87, 92]. VR can be used for reminiscence therapy (the discussion of past experiences with other people to improve well-being [136]), by immersing patients in familiar environments in VR [114, 125, 137], and is a more attractive way to reminisce than pictures [137].

All these prior works demonstrate that technology has the ability to impact users' memory and that HCI is currently heavily engaged in providing tools to enable such. However, our work aims to understand how future memory tools would look like in XR, and provide a critical reflection on potential abuse and opportunities.

### 3.2 Risks of Offloading Memory

Although these memory aids have many benefits, researchers started to question whether such technologies could impair memory [25, 38, 98, 107] and pose safety and privacy issues [10, 31]. First, recording tools can divide attention, and affect how events are encoded [38, 53]. Additionally, being able to remember everything through a total externalization of memories can have negative effects (e.g., the inability to move on after a breakup), which should be considered in the design of such technologies [105]. Clinch et al. identify two potential risks associated with memory externalization: *inhibition* (retaining less information by ourselves) and *distortion* (errors in what and how we remember) [25]. Researchers showed that offloading memories to external media exposes them to manipulations (e.g., altering pictures), which can lead to the creation of false memories (i.e., a strong confidence in the memory of an event that did not actually occur) [25, 86, 98, 134]. These questions of memory manipulations are still new and mainly focused on more traditional media like pictures. Our work explores how new immersive technologies like XR could be used to manipulate users' memory.

### 3.3 Perceptual Illusions and Manipulations

XR devices create visual, auditory, and haptic stimuli, which facilitates control over what users perceive. XR is based on illusions [47] and the creation of immersive virtual environments, in which users have a sense of presence [36, 117]. Having a plausible virtual environment was also shown to make users behave realistically (e.g., plausibility illusion [103, 115]), and feel like their virtual avatar has become a part of their body (e.g., embodiment illusion [119]).

These illusions enable the implementation of a variety of perceptual manipulations, such as VPPMs [126], which leverage visual dominance [95] and unawareness of sensory discrepancy [130] to influence physical actions. Redirected walking [97, 122, 123] and haptic retargeting [5, 23] techniques can steer users' physical walking paths and hand movements by imperceptibly manipulating the virtual scene. Mhaidli et Schaub also identified manipulation techniques unique to XR that could be used for advertising purposes [83] (e.g., altering what consumers see to bias their consumption behavior). Although these manipulation techniques could be beneficial for users (e.g., VPPMs enhancing VR experience), researchers started to explore how they could be exploited maliciously to harm users [19, 83, 126], and how users would react to such attacks [22].

While most of these perceptual manipulations target to have an immediate impact on the user, XRMMs have the potential to have longer-term impacts, through the AM functions (section 2.1.1).

### 3.4 XR Memory Manipulations

These XR perceptual manipulations are possible because users' behaviors in the virtual environment are similar to real behaviors. Studies showed that the encoding and retrieval processes of virtual events are similar to those of real events, making VR an ideal tool for studying real-life cognition under controlled conditions [63, 73, 94]. Particularly, immersion, embodiment, and sense of presence enhance memory encoding and retrieval [12, 34, 77, 90, 118].

While false memories have traditionally been studied using narratives and pictures, Segovia et al. showed that immersing preschool children in a virtual experience can generate false memories [109]. As pointed out by Aliman et al., combining the capacity of AI to generate deepfakes with the capacity of VR to create durable memories could be used for malicious creation of false memories [4].

HCI research focused on how to compensate and overcome memory limitations, and what risks could represent such techniques. However, little work has explored how technologies could leverage memory limitations to achieve other purposes. An example of such work is *Mise Unseen*, which takes advantage of visual memory failures and the change blindness effect to implement a redirection technique in VR [79]. Friedman et al. introduced a method to give people the illusion of time travel in VR, which can have an impact on implicit morality and evaluation of past events [45], and Cuperus et al. showed that manipulating replays of events in virtual reality can alter the memory for sport performances and impact the feeling of competence [29]. While all these prior works demonstrated that XR has the ability to manipulate memory and is potentially more powerful than traditional media, they were individual examples of such XRMMs. In this work, our goal is to have a holistic and deeper understanding of all the types of XRMMs that are possible and discuss their potential impact on the user.

## 4 METHOD

To broadly explore potential XRMMs, we ran three speculative design workshops, bringing together XR and memory researchers. As XR has not yet become a prevalent technology like smartphones, speculative design methods allowed us to explore XRMMs and reflect on their ethical implications, without being restrained to the current usage and capabilities of XR. In this workshop, experts were asked to individually generate XRMM scenarios. These scenarios are grounded in experts' knowledge about XR and human memory, and in the background that was given (section 2). In the discussion phase, we asked experts to select the most promising scenarios and to discuss the likelihood of such scenarios and their potential outcomes (25 scenarios discussed, presented in Table 3). Finally, we applied thematic analysis to uncover underlying themes and mechanisms used.

### 4.1 Participants

Twelve experts (age:  $M = 28.7$ ,  $SD = 4$  yrs) participated in our workshops (Table 2). As the goal was to explore scenarios of XRMMs, we recruited two types of experts: HCI researchers specialized in XR ( $n=6$ , called XR experts), and cognitive psychology researchers studying human memory ( $n=6$ , called memory experts). We ran the workshop three times, inviting each time two memory experts and

	ID	Age	Gender	Profession	Years in Profession
Session 1	PXR1	25	Female	HCI researcher	1
	PXR2	28	Male	HCI researcher	5
	PM1	24	Female	Cognitive engineer	3
	PM2	24	Female	Cognitive psychology student	4
Session 2	PXR3	33	Male	HCI designer	10
	PXR4	33	Male	HCI researcher	4
	PM3	26	Female	Cognitive psychology researcher	3
	PM4	30	Male	Cognitive psychology researcher	8
Session 3	PXR5	27	Male	HCI researcher	6
	PXR6	27	Male	HCI researcher	5
	PM5	38	Male	Cognitive psychology researcher	2
	PM6	30	Male	Cognitive psychology researcher	2

**Table 2: Demographic of experts in XR and cognitive psychology**

two XR experts. This configuration enables to have both a discussion between two experts of the same field, and between experts of different fields. We specifically recruited cognitive psychology researchers who have already used XR, to make sure that they have some basic understanding of what is XR, how it can be used and what new possibilities these technologies offer. Most of the memory experts rated their XR knowledge to be at least average and mostly above average (5-point Likert scale,  $M = 3.8$ ,  $SD = 0.4$ ). Each group of experts rated their knowledge to be at least above average and mostly very high in their expertise field ( $M = 4.6$ ,  $SD = 0.5$ ). The experts were remunerated 30 euros for taking part in the workshop. Sessions were conducted over zoom using Miro as a brainstorming tool. During the last session, PM6 disconnected half-way in the workshop and could not reconnect. The data that was created until the disconnection was included in the analysis.

## 4.2 Workshop Procedure


Step	Goal	Duration
INTRODUCTION	Create a common understanding of <ul style="list-style-type: none"> <li>human memory</li> <li>XR technologies</li> </ul>	20 mins
BACKGROUND	Presenting one set of memory limitations	A/B: 10mins C: 3mins
INDIVIDUAL BRAINSTORMING	Generating XRMM scenarios	A/B: 15mins C: 5mins
DISCUSSION	Presenting scenario <ul style="list-style-type: none"> <li>Evaluating from a technical/cognitive perspective</li> <li>Classifying harm or benefit.</li> </ul>	A/B: 35 mins C: 12mins

**Figure 1: Description of the workshop procedure including steps, goal and duration. The blue square show the three rounds. The red A,B,C point the time for each round.**

Each workshop session lasted three hours and was composed of four experts and one moderator. It consisted of an introduction, and three rounds of introduction to memory limitations, individual brainstorming, and discussion (Figure 1).

**4.2.1 Introduction.** To create a common understanding of the different fields, we gave a detailed introduction on human memory (types, process, functions, and limitations, section 2.1) and XR technologies (section 2.2). We warned participants that this background was not exhaustive, and they were invited to refer to their own knowledge and expertise.

Each round of brainstorming and discussion was focused on one set of memory limitations (forgetting, distorting and persistence, Table 1). We chose to separate the workshop sessions into three rounds so that every different type of memory limitation can be equally explored. The order of rounds between workshops was counterbalanced using a latin-square.



**Figure 2: Scenario template - Miro board screenshot. This template was used by participants during individual brainstorming sessions to generate scenarios.**

**4.2.2 Individual Brainstorming.** Experts were asked to generate as many XRMM scenarios as possible by filling a template (Figure 2). The goal of this template was to help the experts to give more details about the scenarios: who would use the XR application and why? What is the aim of the manipulation and how is it implemented? The experts were free to go beyond that template.

**4.2.3 Discussion.** During the discussion phases, each expert had two minutes to present a scenario in more depth. They were instructed to select scenarios for discussion that they deemed to be the most interesting and valuable. The other experts and moderator could ask questions about the scenario and add comments. Then, each expert rated three aspects of the scenarios (possibility to implement such XRMMs from a (1) technical and (2) cognitive perspective and (3) classify harm or benefit), to trigger discussions. This phase was recorded to be transcribed.

### 4.3 Data Collection

Overall, participants generated 74 scenarios. 25 of them were presented and discussed by the participants during the workshop. We provide a short description of these scenarios in Table 3. The coding was conducted on the transcripts of these 25 discussions. The remaining 49 scenarios existed as templates filled in the Miro board but could not be explained and discussed in detail during the workshop due to time limitations. As these scenarios were often incomplete and lacked details to be fairly represented, we did not use them for the coding sessions, and we do not provide them in this paper. However, some of these non-discussed scenarios contained enough information to derive high-level constructs from them. These scenarios were used in a final session to count the number of scenarios matching the XRMMs definition (section 4.5) and to validate the classes found with the coding.

### 4.4 Thematic Analysis

To analyze the data, three authors conducted synchronous collaborative coding sessions (7 sessions each taking 4 hours, 28 hours in total). In a first meeting, the three coders started by creating an initial codebook (deductive coding) around questions of interest (who is involved in the manipulation, how does it work and why is it used). Afterward, each coder read through all the transcripts of the 25 discussed scenarios without coding them. Then, during 4 meetings, the three coders discussed each scenario. The scenarios were coded following 1) the initial codebook and 2) an open coding procedure (inductive coding). Once a new code that was not covered by the existing codebook came up, the coders discussed this new code, which was added only if all the coders reached an absolute consensus. In the last two sessions, the created codes were structured into themes and connected to larger structures and concepts, resulting in our framework and classes of XRMMs. Conflicts were resolved during the meetings by discussing individual perspectives on every codes and themes until reaching a consensus.

### 4.5 Scenarios Exclusion

After the final coding, we derived a definition of XRMMs (section 5.1) which we used to filter scenarios that did not match the definition. This resulted in 3 of the discussed scenarios to be removed (S23, S24, S25, Table 3), because they do not intend to impact memory, and they are not based on memory limitations. In the scenario S23, advertisements are added in users' field of view to give visibility to brands, but there is no clear intention to distort memories or to influence the cognitive process of memorization. The scenarios S24 and S25 both leverage individual user preferences (i.e., smells and cultural items) to make them appreciate a product, without having an impact on memory. 15 of the non-discussed scenarios did not match the XRMM definition for the same reasons, and 8 did not have enough description to be understood. We obtain a total of 48 scenarios of XRMMs (22 discussed and 26 non-discussed). In the following, the scenarios we refer to are the 22 discussed scenarios of XRMMs (S1 to S22, presented in Table 3).

## 5 RESULTS

Based on our initial questions of interest (who is involved in the manipulation, how does it work and why is it used) and the resulting

themes and codes, we present a definition of XRMMs, a framework of their core components and three classes of XRMMs.

### 5.1 Definition of XRMMs

To provide a definition of XRMMs we first needed to provide a general definition of perceptual manipulations, and then show how XRMMs are different from other types of perceptual manipulations, such as VPPMs [126].

**Definition of Perceptual Manipulations:** *Perceptual manipulations are mechanisms grounded in limitations of users' cognition and perception with a clear intention to influence users towards a specific outcome.*

This general definition is classifying PMs as a mechanism (defined by Webster dictionary as "a process, technique, or system for achieving a result"<sup>1</sup>) and describing the two core components of perceptual manipulations: (a) a grounding in cognitive and perceptual limitations and thresholds and (b) a clear intention to steer towards a specific outcome. The outcome could be effecting change in beliefs, attitudes, intentions and resultant behaviour/responses - or influencing any other cognitive and affective response. We kept this definition open to be able to include all future types of perceptual manipulations. Grounded in our analysis of the different classes of XRMMs and their core components, we created the following definition of XRMMs.

**Definition of XR Memory Manipulations:** *XRMMs are perceptual manipulations grounded in memory limitations with the intention to impact memories, leading to long-term effects on users, through the self, social and directive functions of autobiographic memory.*

The intention of impacting users' memory allows us to distinguish XRMMs at the stage of encoding from general perceptual manipulations, and to distinguish XRMMs from VPPMs [126].

**Definition of Virtual-Physical Perceptual Manipulations:** *VPPMs are perceptual manipulations that are grounded in visual-haptic limitations with the intention to nudge the user's physical movements*

### 5.2 XRMMs Framework

We found that five core components were able to describe the intentions and structures of XRMMs: *the context, the memory mechanisms, the implementation, the memory functions and the final goal* (Figure 3). These components were part of all the generated scenarios.

**5.2.1 Context.** XRMMs are done in a certain context. There is a *manipulated*, who is the target of the manipulation, a *manipulator*, who is at the origin of the manipulation, and an *XR application* within which the manipulation is occurring.

10 out of 22 scenarios are targeting a vulnerable population (e.g., people suffering from trauma or memory problems). This

<sup>1</sup>"Mechanism" by Webster dictionary: <https://www.merriam-webster.com/dictionary/mechanism>



## Framework of XR Memory Manipulations




Figure 3: Framework presenting the five core components of XRMMS

population can benefit from XRMMS (e.g., to treat a trauma), but they can also be harmed.

In 6 out of 22 scenarios, the manipulator and the manipulated were the same person. In this case, the user is manipulating themselves through XR, knowing that the results of the manipulation would benefit them. When the manipulator is not the manipulated, the scenarios represent three types of manipulators: people in power, businesses, and attackers. These actors are always using XRMMS for their own interest.

Finally, as XRMMS are based on XR technologies, they are always done within an XR application. In the scenarios that were generated, the XRMMS are done within various types of applications (e.g., training applications, social media, entertainment, therapy tool, etc). The purpose of the application is not necessarily the same as the purpose of the manipulation. In this case, the user is often not aware of the manipulation.

**5.2.2 Memory Mechanism.** XRMMS are relying on memory mechanisms. In this work we focus on long-term memories, and we grounded the workshops in the seven memory limitations presented by Daniel Schacter (Table 1) [106]. These limitations can either be *leveraged* (taking advantage of memory limitations to manipulate it), or *prevented* (using XR to overcome these limitations). 14 scenarios are leveraging memory limitations (for both positive and negative purposes), and 8 scenarios are preventing them (for positive purposes only). Each of the seven memory limitations were explored by the scenarios. 3 scenarios focused on transience, 4 on absent-mindedness, 1 on blocking, 7 on misattribution and suggestibility, 3 on bias and 4 on persistence. We found that depending on the moment when the manipulation takes place in relation to the memory process (*at encoding, pre-retrieval, at retrieval*), and depending on the type of memory limitation that is leveraged, different implementations and strategies are used. This constitutes three *classes of XRMMS* which are described in sections 6, 7 and 8.

**5.2.3 Implementation.** We found a split between types of implementation (AR and VR techniques) that are used. In AR, XRMMS can be implemented by *adding digital elements to the real world* (e.g., adding a frame around an object), by *removing elements from the real world* (e.g., hiding an object), or by *modifying elements* (e.g., replacing a real object by a different virtual one). In VR, manipulations can be done by *immersing users in a new environment*, or in a *3D reconstruction of a past event* that they already experienced before. This reconstruction can either be accurate or altered. In sections 6, 7 and 8, we present what implementations are used depending on the memory mechanisms involved.

**5.2.4 Outcomes.** This context and memory mechanisms, associated with an implementation, can influence the cognitive processes associated with the encoding or retrieval of memory, or influence the perception of past events. This manipulation can *impact users through the three functions of AM* (section 2.1.1) [14]. The scenarios explore how XRMMS can have an influence on self-perception, preferences and emotional state (related to the self-function of AM), on relationships and empathy (related to the social function), and on decisions and behaviors (related to the directive function).

Impacting users through the memory functions (self, social and directive) enables to achieve a *final goal*. For example, XRMMS could be used to influence decisions (impact through the directive function), with the final goal to make someone buy a product, or it could be used to have an impact on self-confidence (e.g., impact through the self-function), with the final goal to help someone perform better in a task. From the scenarios, we identified four main types of final goals: purely malicious goals (e.g., creating chaos), making money (e.g., selling a service or a product), improving mental state (e.g., coping with traumas), and self-optimization (e.g., performing better in a task).



## Classes of XR Memory Manipulations




Figure 4: The three classes of XRMMs (*at encoding, pre-retrieval, retrieval*), which differ in terms of *technology used*, and *impact on memory*. Two examples of mechanisms (*How, Example scenarios*) are given for each class.

### 5.3 Threat Model

Grounded in the “manipulator” theme of our framework, we derived a threat model outlining future abusive scenarios. An attacker wants to influence a user’s future decisions, social interactions, or self-perception (section 2.1.1), by leveraging memory manipulations in XR (XRMMs). To achieve this, the attacker needs access to the software of the device, and to be able to control its function (e.g., access to the user’s data, the device’s sensor data, and control over device output). We outline three routes towards enacting such a threat that emerged from our dataset:

**Non-consensual manipulation** by tricking the VR user into installing malware (e.g., similar to current approaches in smartphones, as done in the Pegasus spyware<sup>2</sup>). This can be seen in scenarios S3, S13, S17, S19, and S20, where a hacker gains control over a user’s software.

**Exploiting a position of power** by having access to the device from a position of power and authority (e.g., by being a caretaker of a person using VR as a therapy tool, as in scenarios S7, S8, S10, and S11).

**Consensual, incentivized manipulation** by gaining the user’s permission (e.g., making the user accept to be manipulated in exchange for free services). With the rise of computing technology and social media, we accepted a new form of direct marketing and advertising that is tailored directly toward the individual consumer and leverages psychological principles such as those outlined in dark design patterns. Similar business models could potentially be done with XRMMs (as seen in scenarios S1, S12, S15, and S18). This opens a potential threat around the user willingly accepting a method that is actively influencing their memory as a “currency” to get access to a service (similar to today’s approach of “paying” for social media with our data).

### 5.4 Classes of XRMMs

After coding each scenario we noticed one set of codes focusing on the moment when the manipulation occurs. Knowing the stages of formation of long-term memories (encoding, storage and retrieval, section 2.1 [82, 112]), we were able to identify three moments when a manipulation can occur: while the event is happening (*at encoding*), while it is remembered (*at retrieval*), or between encoding and retrieval (*pre-retrieval*) (Figure 4). All of the generated XRMMs scenarios fall into one of these three categories. In 6 scenarios, the manipulation occurs *at encoding*, 14 others occur *at retrieval*, and 2 others occur *pre-retrieval* (Table 3). After analyzing these scenarios, we found three main classes of XRMMs that differ in terms of technology and impacts: 1) manipulations *at encoding* aim at *influencing the quality of memory encoding* and rely mainly on the *capacity of AR to visually alter (add, remove, modify) reality*; 2) manipulations *at retrieval* aim at *distorting the perception of past events* and rely mainly on *immersive reconstruction of scenes in VR*; 3) manipulations *pre-retrieval* aim at *inducing forgetting*, using both AR or VR specific abilities (Figure 4).

In the following, we present each XRMM class by providing examples of scenarios generated during the workshop and grounding them in cognitive psychology research. For each class, we present two examples of ways to impact memory (“How” in Figure 4). These are just examples of mechanisms that were explored during the workshops, other mechanisms could be explored by future research. To improve readability, we will not only present the classes as results but add an explanation and interpretation as would usually be done in a separate discussion section. Our final discussion will focus on the larger concept of XRMMs and perceptual manipulations.

<sup>2</sup>Pegasus, smartphone spyware [https://en.wikipedia.org/wiki/Pegasus\\_\(spyware\)](https://en.wikipedia.org/wiki/Pegasus_(spyware))




Figure 5: Illustration of “This You Should Remember” (S6). Louise uses AR to better encode important information. Figure A illustrates the unaltered field of view, a scene crowded with visual stimuli. Figure B illustrates in green how the AR application is occluding the elements that are considered by the system as distractions, and in pink how information that are considered worth remembering are emphasized.

## 6 XRMMS AT ENCODING

The first moment when a memory can be manipulated is *at encoding*, simultaneously as the original perception of the event. The encoding phase is important because it determines what will be stored in long-term memory, and how it will be stored [82]. Therefore, acting at encoding could enable to act on the quality of the memory. From the 6 out of 22 discussed scenarios of XRMMS at encoding, we found that these manipulations could be done *by inducing emotions* or *by steering attention* (by preventing or leveraging absent-mindedness), mainly using AR. We found that XRMMS at encoding could be used to help encode better quality memories, but it could also be used for the opposite purpose: to deliberately make someone’s memories weaker. In the following, we explain and discuss these two means to influence encoding: *inducing emotions* and *steering attention*.

### 6.1 Influencing Encoding by Inducing Emotions

Two scenarios (S1, S2, presented in Table 3) explore how XRMMS could influence encoding by inducing emotions.

**6.1.1 Grounding.** Emotions modulate every aspect of cognition, and particularly memory [127]. It is established that the emotions

felt during an event influence the retention and recall of the memory: experiences linked to strong emotion are retained longer, more vividly and accurately [17, 93, 127]. While some studies indicate that positive emotions facilitate learning [128], negative emotions such as stress or fear can also facilitate or alter the quality of memory encoding, depending on the intensity of the emotion [81, 133].

**6.1.2 Scenarios.** In the scenario “You’ll Remember the Unlikely Risky Event” (S2), XR is used to induce strong emotion in a learning context, so the information is better encoded and remembered later (e.g., stimulating an accident while learning how to drive in VR). Another scenario, “Peak-End Rule” (S1), uses XR to induce intense positive emotions, which will be better remembered than the negative ones and improve user’s self-perception.

### 6.2 Influencing Encoding by Steering Attention

Four scenarios (S3, S4, S5, S6, presented in Table 3) explore how XRMMS could influence encoding by steering attention with AR, preventing or leveraging absent-mindedness.

**6.2.1 Grounding.** The encoding of memories is selective: we are constantly exposed to large quantities of stimuli from our senses,

but since storing all this information is impossible, we make a first selection at encoding [27, 32, 129]. Absent-mindedness (Table 1) is when forgetting occurs because insufficient attention is given at encoding (e.g., because of mind wandering or divided attention) [6, 13, 28, 106]. This can be observed in situations when people forget where they left their glasses, because it is the kind of task that is carried out automatically, without paying enough attention.

**6.2.2 Scenarios.** “This You Should Remember” (S6) depicts well how absent-mindedness could be prevented or leveraged. In this scenario, Louise has AR glasses and uses them to offload some cognitive tasks. The AR application chooses for her what is worth remembering, and steers her attention towards it, so it is better encoded. Thanks to the AR glasses’ ability to visually alter reality (adding content, removing or modifying), important elements in the environment are framed or highlighted, and the non-important distractions are blurred (Figure 5). Detecting and deciding which are the important elements is done through an AI process, based on crowd-sourced data. The application is preventing absent-mindedness by helping Louise to focus on important things to be remembered. It is also leveraging absent-mindedness, to limit the encoding of events deemed unworthy. Two other similar scenarios were generated (S4 and S5), where inattention is detected using biometric or neurological signals, and attention is directed using visual feedback in AR or by hiding distractions.

## 6.3 Discussion

**6.3.1 Technological Challenges.** In scenarios S1 and S2, influencing the quality of memory encoding relies on the capacity of immersive environments to induce emotions. Since VR can induce vivid emotions and reactions similar to real events [41, 78, 115, 140], these manipulations are technically plausible. The scenarios influencing the quality of memory encoding through attention steering rely on the capacity of AR to visually alter reality. As research focusing on how to alter or diminish reality in real time shows promising results [11, 24, 54, 85], such manipulations are plausible in a near future from a technological perspective. Another technical challenge for such manipulations is the ability of AI tools to identify in real time what represents a distraction and what is important. However, research in the direction of object detection and identification in images made a lot of progress these last years [132, 139].

**6.3.2 Role of XR.** During the analysis, we additionally coded currently existing techniques that would have a similar impact on the encoding of memory. We found that influencing memory encoding by inducing emotions is not unique to XR, and scenarios similar to S1 and S2 could be implemented using smartphone applications. However, the capacity of XR to fully immerse the user in an environment allows to induce vivid strong emotions [41, 78, 115, 140], which could amplify this type of manipulation. We also found that the current techniques to steer attention (e.g., noise-canceling headphones or focus mode on smartphones), cannot visually steer users’ attention. XR (and AR in particular here) is unique in its ability to visually alter the perception of the real world. Using this could enable to interfere with the encoding process more effectively than most currently known techniques.

**6.3.3 Purpose.** The generated scenarios suggest that XRMMS at encoding could help and benefit AR users. In four scenarios (S2, S4, S5, S6), the goal of XRMMS is to optimize brain capacities and offload cognitive tasks. PM3 mentioned that such techniques could be used by healthy users but could also help people suffering from Attention Deficit Disorders (ADD). However, another scenario (S3) relies on the same idea of influencing encoding through attention, but with the opposite purpose. In this scenario, distractions are added to the field of view of the person wearing AR glasses to make their memory encoding weaker, and make them vulnerable to attacks. While the intentions behind the previous scenarios were positive, this scenario depicts a malicious use of XRMMS at encoding.

## 7 XRMMS AT RETRIEVAL

A memory can be manipulated *at retrieval*, while it is being remembered. Memory storage is dynamic: memories are susceptible to change when they are retrieved, and retrieval leads to the formation of new memories [2, 3, 104]. Therefore, acting while a memory is remembered could enable to act on its perception, and distort it. From the 14 discussed scenarios of XRMMS *at retrieval*, we found that these manipulations could be done *using VR reconstructions of past events as a reflection tool* (to leverage positivity bias and prevent persistence), or *using distorted reconstructions* (leveraging misattribution and suggestibility). We found that XRMMS *at retrieval* could be used to influence someone’s perception of the past for various positive purposes (e.g., to prevent suffering), but it could also be used to make someone vulnerable. In the following, we explain and discuss these two means to influence perception of the past and distort memories: *supporting reflection* and *inducing suggestions*.

### 7.1 Influencing Perception through Reflection

Five scenarios (S7, S8, S9, S10, S11, S12, S13, presented in Table 3) explore how XRMMS *could influence perception of past events by using VR as a reflection tool, preventing or leveraging bias and persistence*.

**7.1.1 Grounding.** Reflection is the process of reviewing past experiences to learn from it and to reframe it. Memories can be actively reviewed through this process [66]. While reflecting on positive events increases the ability to enjoy life and helps to perceive things more positively [16], reflecting on negative events (e.g., being confronted to traumatic events) can help to cope with them on the long-term [91]. Reflection can be done without employing technology by mentally reviewing memories of past personal experiences, or using technologies support, by reviewing rich digital records of past events (e.g., text, images or videos) [57, 65].

**7.1.2 Scenarios.** “Therapy” (S8) depicts how VR could be used to reflect on past experiences and reframe them. In this scenario, a patient is immersed in a VR reconstruction of a past event that they are discussing with the therapist. This reconstruction helps the patient to retrieve the memories of that event, and analyse the situation with the information that they have now but they did not have when the event occurred. “Couple Game” (S9) and “Dysmorphia” (S10) also explore that direction, respectively to help couples communicating, and to correct self-perception. “Traumatic Memory” (S7) shows how a therapist could use VR as a tool to treat a patient suffering from Post-Traumatic Stress Disorder (PTSD), by



**Figure 6: Illustration of the scenario “Buy a Friend” (S18). Jim inserts himself in the VR album of Jenny’s party, to distort her memory and make her remember he was there. In blue the participants that were present at Jenny’s party, in orange the hand of Jim editing the VR reconstruction of the party, in pink the insertion of the 3D capture of Jim inside the party, in green the altered parts of the reconstruction.**

immersing to them in the context of the trauma. This method, called Virtual Reality Exposure Therapy (VRET), is already explored and shows promising results [33, 46, 111].

However, even if being exposed to traumatic memories can be benefiting on long-term, it can also be harmful on short term. Two scenarios (S12, S13), explore how malicious actors could expose VR users to traumatic events to make them suffer out of malicious intend or make them uncomfortable with the intention to sell an option which could prevent future exposure.

## 7.2 Distorting Memories through Suggestions

Seven scenarios (S14, S15, S16, S17, S18, S19, S20, presented in Table 3) explore how XRMMs could distort memories by using altered 3D reconstructions of past events, leveraging misattribution and suggestibility.

**7.2.1 Grounding.** Misattribution is when a memory is present in mind but attributed to the wrong source (Table 1) [106, 108]. This

effect occurs because a memory is not labeled with its source: it is unconsciously deduced during retrieval, from different cues. If these cues are not precise enough, the right source cannot be retrieved [60, 61]. A good example of misattribution is when someone think they remember an event they experienced, when they actually just remember the picture of that event. Suggestibility refers to the fact that memories can be distorted if a new information is added between encoding and retrieval, through leading questions or comments [75, 76, 106]. It is related to misattribution because distortion from suggestion always involves some misattribution between the real event and the suggested information.

**7.2.2 Scenarios.** “Buy a Friend” (S18) depicts well how misattribution and suggestibility could be leveraged. In this scenario, Jim uses a VR social media application where immersive reconstructions of past events can be revisited and shared with other users. With his premium account, Jim has the possibility to insert himself in other peoples’ memories. As he wants to get closer to Jenny but

could not go to her last party, he decides, through the application, to insert a realistic 3D representation of himself in the memories that Jenny shared (Figure 6). Later, when Jenny revisits her memory in the application, she sees that Jim was there. Because of misattribution (between the reconstructed event and the real event) and suggestibility (integrating the suggested information that Jim was there), Jenny’s original memory might be distorted: “Jim was there too, we had such a nice time together.” In this scenario, the social media business sells a service that uses XRMMS at retrieval. Six other scenarios (S14, S15, S16, S17, S19, S20) also rely on the similar idea that altered 3D reconstructions of past events could be used to overwrite and distort the memory of the original event.

### 7.3 Discussion

**7.3.1 Technological Challenges.** The main technological challenge of the scenarios of XRMMS *at retrieval* is the ability to make 3D captures of events. As volumetric capture techniques are already being developed and show good results [42, 74], this is plausible from a technological perspective. The manipulations aiming at distorting memories imply the ability to alter the 3D reconstructions of past events (e.g., inserting someone in a VR memory, S18). This could be done manually with some time and efforts, but represents a technological challenge to be automated. However, recent advances with inpainting methods [88, 96] and generative AI tools, such as Stable Diffusion [121] or DALL·E 2 [89], suggest that this would be plausible in a near future.

**7.3.2 Role of XR.** Influencing the perception of the past through reflection is not unique to XR, as it can be done without technological support, or by using pictures and videos [57, 65]. However, VR represents a more attractive way to reminisce [137] and enhances episodic memory performance [77, 118], which could facilitate this type of manipulation. Distorting memories through suggestions could already be done using pictures (e.g., the scenario “Buy a Friend” (S18) could be done by inserting people in pictures shared on social media) [86, 98, 134], but the realism and embodiment enabled by XR could amplify the misattribution effect. In the Reality Monitoring framework, Johnson and Raye identify the cues used at retrieval to differentiate between external (real) and internal (imagined) events [60, 61]. Memories that have a lot of sensory characteristics (e.g., tactile, olfactory), semantic content (e.g., detailed colors, shapes) and contextual information (e.g., spatial, temporal) are more likely to be memories of external events. However, an internal event that has plenty of characteristics corresponding to an external event (e.g., rich in perceptual details) is likely to be confused with an external event. The Reality Monitoring framework can be combined with media richness theory to explain why one could assume that increasing the “richness” (e.g., modalities, visual quality) of VR experiences might also lead to being more vulnerable to misattributions between real and virtual experiences [43, 55, 56, 102, 109]. Segovia et al., were able to demonstrate that using VR to induce false memories in elementary school children is more effective compared to the baseline condition [109]. Although distorting memories can be done with more traditional media like pictures, using VR to induce suggestions could be more efficient and amplify the effect of the manipulation.

**7.3.3 Purpose.** This class of manipulation can serve various purposes. Immersive reconstructions of past events could be used as a reflection tool to understand the past better and reframe it more positively to prevent suffering (e.g., S8). PM1 suggests that such manipulations should only be done by a professional third party (e.g., a therapist), as immersing users in reconstruction of traumatic memories could also be harmful (e.g., S13, S12).

Even though in two scenarios (S14, S16) altering reconstructions of past events benefits the user (e.g., in S14, a VR user distorts their own memories to have a better impression about their past and increase their confidence), in three other scenarios (S15, S17, S20), the XRMMS serve malicious purposes (e.g., selling something from deception or making someone feel incompetent). In the scenario “Buy a Friend” (S18), the initial intention is positive, as the goal of the manipulation is to help someone make friends. However, this friendship would be based on false memory induction, which is not “ethically great”, according to PM3. Furthermore, this manipulation could be used to get close to someone with malicious intentions (e.g., to get money from them). These scenarios raise ethical concerns about the possibility to alter the 3D reconstruction of past events.

## 8 XRMMS PRE-RETRIEVAL

Finally, a memory can be manipulated *pre-retrieval*: after the event occurred, but before it is remembered. From the two discussed scenarios of XRMMS *pre-retrieval*, we found that these manipulations could *induce forgetting*, either by *hiding memory cues* (leveraging transience), or by *inducing stress* (leveraging blocking). Inducing forgetting could be done for positive or negative purposes (e.g., to help someone forget a negative experience, or to make them feel incompetent). As XRMMS pre-retrieval are described in only two of the discussed scenarios, this direction should be explored in more depth. In the following, we explain and discuss these two means to induce forgetting: *hiding memory cues* and *inducing stress*.


### 8.1 Inducing Forgetting by Hiding Memory cues

One scenario (S21, presented in Table 3) explores how XRMMS *could induce forgetting by hiding memory cues, leveraging transience*.

**8.1.1 Grounding.** Transience refers to a weakening or loss of a memory over time (Table 1) [106]. Memories from a few minutes ago are naturally more precise and vivid than memories from years ago [37]. Transience can be reduced by retrieving memories often (e.g., thinking or talking about it). Memories that are rarely or never recalled will be forgotten more quickly [7, 106, 124].

**8.1.2 Scenario.** The scenario “AR Eraser” (S21) explores how AR could be used to leverage transience and help someone to forget an unwanted memory. In this scenario, Alex uses AR glasses to hide in their environment all the elements associated with their former partner, which they want to forget faster. These elements could either be blurred (e.g., blurring the bench where the couple had their first kiss), or replaced (e.g., replacing a picture by another one) (Figure 7). By hiding memory cues linked to that person, the thoughts linked to them could be less frequent and the memories could degrade faster.





**Figure 7: Two illustrations of the scenario “AR Eraser” (S21). Alex uses AR to hide the elements associated with their former partner, to forget them faster. Figures A1 and B1 show the unaltered situation. In A1 a photo of Alex and his former partner, and in B1, the bench where they kissed for the first time. A2 and B2 shows what Alex sees with the AR glasses, replacing the elements that might reinforce the unwanted memory. In pink are the replaced elements, in green are the visual area impacted by the alteration.**

## 8.2 Inducing Forgetting by Inducing Stress

One scenario (S22, presented in Table 3) explores how *XRMMs could induce forgetting by inducing stress, leveraging blocking*.

**8.2.1 Grounding.** Blocking is when a memory is encoded and stored in mind but cannot be retrieved when needed (Table 1) [106]. An example of blocking is the “tip of the tongue” state, when we cannot remember a word, but we can produce partial information about it, like its first letter. These retrieval failures can occur due to stress [64, 135].

**8.2.2 Scenario.** The scenario “False Training App” (S22) explores how blocking could be leveraged to make VR users vulnerable. In this scenario, Paul uses a VR application that proposes to test his knowledge (e.g. a quiz application). This application immerses users in a stressful environment (e.g., showing a crowd around the user) to intentionally trigger blocking and make them fail the test and feel incompetent. The application then proposes the user to buy a training application, to gain more competence.

## 8.3 Discussion

**8.3.1 Technological Challenges.** The “AR Eraser” (S21) scenario relies on the ability of AR to diminish reality and hide elements, which is already explored and partially plausible from a technological perspective [24, 54, 85]. This manipulation also requires AI-backed tools to identify and select the elements which need to be altered

(in this scenario, the elements related to a former partner), and to alter them seamlessly. This represents technological challenges, but research about object detection in images [139], inpainting [96], and generative AI [89, 121] shows promising results.

**8.3.2 Role of XR.** Although the technique used in the scenario “AR Eraser” (S21) to induce forgetting is already physically feasible without AR for personal objects (e.g., storing every object related to a person in a box out of the user’s view, or removing someone from a picture), AR is unique in its ability to hide elements that the user cannot physically remove (e.g., a bench on the street), which makes this manipulation more complete and effective.

The “False Training App” (S22) scenario relies on the capacity to induce stress. It could already be implemented on smartphone applications (e.g., by adding stress factors usually used in games), but VR allows to fully immerse the user in a stressful environment, which can trigger realistic physiological reactions [67, 78, 140]. This specificity of VR could amplify the blocking effect and make this manipulation easier to induce.

**8.3.3 Purpose.** The intention behind the scenario “AR Eraser” (S21) is positive, as the goal is to prevent suffering caused by painful memories. However, this technique is questionable, as interfering with natural coping processes could have undesirable effects. PXR2 points out that bad memories “also exist for a reason”, so avoiding them is not necessarily the right solution.

In the scenario “False Training App” (S22), forgetting is induced for malicious purposes (i.e., selling something from deception). This raises ethical concerns about the ability of immersive technologies to induce realistic physiological reactions such as stress.

## 9 GENERAL DISCUSSION

Our main goal with this research was to explore what types of memory manipulations that could become possible in XR (classes), and how the technology is functioning as an enabler or amplifier in these manipulations (framework of core components).

From the thematic analysis of the generated scenarios, we found **that XRMMs can be described by five main components**: the context, the memory mechanisms, the implementation, the memory functions and the final goal. While the context, implementation and final goal are elements found in most other XR applications, the grounding in memory mechanisms and the impact on users through memory functions is a unique property of XRMMs. Similar to perceptual manipulations, the designer of the application needs to understand the limits of human cognition to implement the manipulation and reach the desired goal. However, with memory manipulations, the designer must not only know how to leverage memory limitations, but must also know how they can impact users through the AM functions (self, social and directive functions) to achieve the desired outcome. This indicates that these XRMMs will require a deeper understanding of human cognition and perception during the design and development process.

Additionally, we found **three classes of XRMMs** that are substantially different from each other in terms of technology used (AR vs. VR) and impact on memory (influencing quality of memories, distorting memories, and inducing forgetting). XRMMs *at encoding* rely dominantly on AR technology to interfere with memory building. This class of XRMMs is strongly grounded in the abilities of XR to sense the user and the environment and display digital information over the physical world. XRMMs *at retrieval* rely dominantly on VR technology and the ability to immerse users in 3D reconstructions of past events, to either change their perception of a memory or to distort it. While these manipulations could already be implemented with 2D media such as images, VR is a richer media (relating to media-richness theory [56, 109]), and the encoding processes of VR events are closer to those of real events [63, 118], which could amplify the effect of these manipulations. XRMMs *pre-retrieval* focus on inducing forgetting by hiding memory cues (in AR) or by inducing stress (in VR). This class falls into the same arguments about being potentially more severe than 2D equivalents and enabling new opportunities for impacting users’ memory.

Working with experts from both fields (XR and cognitive science) allowed us to not only uncover these classes and mechanisms but to ground our speculative design method in existing research about human memory. During the discussion of each workshop, experts were able to comment on the likelihood of scenarios but also discuss what potential positive and negative impacts such scenarios might have on the individual and society. In the following, we present a discussion around potential positive and negative directions which are partially coming out of the discussion of the workshop and partially from our own reflection about our work and prior literature.

### 9.1 The Good: One Step Closer to Augmenting the Human Intellect

13 out of the 22 scenarios created and discussed in our workshop were focused on positive applications, either to support a neurodivergent population or to augment the abilities of neurotypical users. Both of these could be seen as the augmentation of the human and in particular the human intellect [39]. Douglas Engelbart presented a conceptual framework focusing on increasing a user’s capability to solve complex problems. He gives a set of examples of what these capabilities might be: *more-rapid comprehension, better comprehension, the possibility of gaining a useful degree of comprehension in a situation that previously was too complex, speedier solutions, better solutions, and the possibility of finding solutions to problems that before seemed insoluble*. These capabilities are partially referring to the directive function of memory. By using XRMMs *at encoding*, a user would have *the possibility of gaining a useful degree of comprehension in a situation that previously was too complex*. Steering the user’s attention (e.g., “This You Should Remember” S6) or inducing emotional stimuli (e.g., “You’ll Remember the Unlikely Risky Event” S2) strengthens the memory of the experienced event and can later lead to better performances due to the directive function of memories. The particularly interesting part of this type of augmentation, compared to Engelbart’s vision, is that XRMMs are not an external tool that is used to perform a task better. XRMMs are a tool to alter perception and memory and thereby change the self, for better or for worse. The main difference is that once the tool is removed, the augmentation still persists, unlike the examples given in “Augmenting the Human Intellect”. This is also a core difference between perceptual manipulations such as VPPMs and XRMMs. XR is presenting a vehicle for these types of manipulations since it is now possible to apply them to the real world and not only on digital information. However, this interference with the human perceptual and cognitive system comes with the price of the loss of *Perceptual Integrity*.

### 9.2 The Bad: One Step Closer to Losing Perceptual Integrity

The concept of *Perceptual Integrity* came up during the joint coding session and the analysis of the free discussions that experts had during the workshops. When discussing the scenario S6 where an AI selects what the user should be attentive to (Figure 5), PXR5 mentioned that if “what is worth remembering is crowdsourced”, users would “lose some part of their individuality”, which might be “harmful for democracy and for thinking on our own”. Realizing this distinction between a temporal augmentation through a tool and a permanent augmentation through something like XRMMs, we discussed the idea that XR is capable of (sometimes even unnoticeably) interfering with our perception of the real and virtual world and thereby undermining our agency and trust in what we are perceiving to be unaltered by technology (perceptual integrity).

This is particularly possible once the human cognitive system is becoming part of the application design and once the developer can leverage known thresholds to steer users towards actions or beliefs through alterations of their subjective reality. The specific danger we see with XRMMs compared to perceptual manipulations such as



VPPMs (e.g., redirected walking [123]) is that XRMMs have a longer-term impact on users. Where redirected walking is leveraging a threshold of the visual system to have an immediate impact on users' physical movements, XRMMs are leveraging weak spots in our cognitive system that are able to impact the users' self-perception, their social interactions, and decisions and behavior, through the three AM functions (self, social and directive, section 2.1.1).

These findings are building on the works of prior researchers that started to have similar concerns around the ability of XR to influence and manipulate users perception. Roesner et al., presented in 2014 [100] and 2021 [99] a set of potential challenges around security and privacy of AR technology. They refer to the construct of perceptual manipulations as “output security” and started to propose structural changes from a security research's perspective on how to enable a safe [69] and secure [70] augmentation. Similar to our interdisciplinary research approach, Baldassi et al., combined neuroscience and computer science in their exploration of the “output challenge” and presented one of the core challenges to the ability of AR to manipulate the users sensory, perceptual and cognitive system [8]. Our findings are adding to this research directions by presenting a more detailed definition of perceptual manipulations in general and a distinction between VPPMs and XRMMs.

Distinguishing these two types of perceptual manipulations in XR (VPPMs and XRMMs) allowed us to discover and articulate the concept of perceptual integrity. XR as a technology mediates our perception of reality. Consequently it strongly influences our perceptual integrity, i.e., the extent to which our perception of reality is sound and accurate. Approaches that manipulate or undermine perceptual integrity using XR have thus far done so with the intent to influence free will, agency and autonomy - impacting our behaviour, actions and reactions in the process. XRMMs and VPPMs are two powerful examples of the potential for manipulating perceptual integrity using XR, and exemplify the new risks posed to perceptual integrity, particularly by the advent of everyday consumer AR. We argue that both types of perceptual manipulations are only working since they are breaking with the idea of perceptual integrity. However, one could argue that VR and AR are at their core manipulating the perception of the user (e.g., visually displaying digital content that does not exist in the physical world).

In addressing perceptual manipulations and their impact on perceptual integrity, our research prompts a breadth of future research questions that researchers need to urgently address before we arrive at the point of ubiquitous XR. In particular: How should we balance perceptual integrity against exploiting the advantages and capabilities that XR-driven perceptual mediation unlocks? To what degree do we allow perceptual manipulations to be applied? What mechanisms are required to make users aware of potential or on-going perceptual manipulations without breaking with the experience? What new types of perceptual manipulations will XR enable, and what opportunities, risks, and concerns do they pose? And perhaps most fundamentally of all, who or what should be able to access and utilize this capacity for perceptual manipulation, and under what circumstances is this regulated by law? Such capabilities can empower individuals - but they could also be used by other entities, from businesses to governments, eager to influence or steer the beliefs, attitudes, intentions and actions of users.

These are all questions that are currently similarly asked in the field of Neurotechnology (technology that interfaces with the users neural system and is able to monitor or modulate neural activities). The Neurorights Foundation presented a set of five rules (Mental Privacy, Personal Identity, Free Will, Fair Access to Mental Augmentation and Protection from Bias) [44]. While all of them do similarly apply to perceptual manipulations, the rule of Free Will (“Individuals should have ultimate control over their own decision making, without unknown manipulation from external neurotechnologies.”) is the best demonstration that perceptual manipulations in XR have similar concerns and should work on a similar set of rules that try to prevent abuse without constraining the powerful abilities of XR. Slater et al., raises similar concerns around the power that realism has in virtual environments [116].

### 9.3 The Ugly: Who is Responsible for the Trajectory and what can the HCI Community do?

An important question that we want to address is about the responsibility and trajectory of perceptual manipulation research. In recent years, perceptual manipulation techniques have been frequently published in the field of HCI and XR, mainly uncovering interaction techniques that could leverage users' perceptual thresholds [5, 97, 122, 123]. While researchers are starting to explore potential harms that could arise from XR and perceptual manipulations [50, 83, 126], these works are mainly arising from the Safety, Security and Privacy community [8, 69, 70, 99, 100]. XR and HCI researchers are still dominantly focusing on the potential benefits of perceptual manipulations and working towards understanding and quantifying new thresholds. A good example is the field of locomotion and redirected walking in Virtual Reality [97, 122, 123]. The majority of publications are focusing on even more precisely detecting the perceptual thresholds of visual rotations. This leads us to the second part of this question: Who is responsible and what can HCI research contribute?

With this paper, we wanted to demonstrate how we imagine future research around perceptual manipulations. We presented a set of weak spots in human cognition that have the potential to be leveraged in XR for positive and negative application scenarios. The emphasis is on having a holistic perspective of potential threats arising from this type of application. The abusive scenarios were not an afterthought but an essential part of this research. Instead of focusing on just the positive applications XRMMs could enable (augmenting the human intellect), we present a more general exploration, including and reflecting on the potential abusive scenarios (e.g., perceptual integrity). With this paper, we want to present how these four important fields (HCI, XR, Security, and Cognitive Science) need to come together and present a critical reflection of their contributions to the scientific field of XR perceptual manipulations.

## 10 LIMITATIONS

Using speculative design workshops comes with the risk of generating scenarios that are more fictional than grounded in our current understanding of a subject. To be able to explore such a construct as XRMMs, we needed to apply this method since the distribution XR consumer devices is not yet at the point where this becomes

possible. However, to still create a strong foundation in the two respected fields (XR and Cognitive Science) we recruited experts from the individual fields and build our workshop around known and existing memory limitations. Additionally, we presented each class of XRMM by giving examples of memory mechanisms which could be leveraged, grounded in cognitive psychology research. These examples are not exhaustive and could be extended by future research about XRMMs. Since we used a collaborative coding approach, we were not able to calculate Inter-Coder Reliability (ICR) measures during the thematic analysis process. Independent coding and ICR would have provided a more objective measure of agreement. However, our collaborative approach allowed to reach agreement through discussion and initiated an early reflection on the data and the codebook. Also, most of the experts participating in the workshop were participating from a Western European country (11 out of 12 participants), but we did not collect any formal information about their cultural background. On this basis, we cannot claim any cultural diversity in the scenarios generated.

## 11 CONCLUSION

In this work we explored how XR could be used to manipulate memory. We ran three speculative design workshops (n=12), with XR and memory researchers creating 48 XRMM scenarios. Through the thematic analysis we arrived at a definition of XRMMs, distinguishing them from other types of perceptual manipulations (e.g., VPPMs). Additionally, we presented a framework of their core components, and discussed three classes of XRMMs (*at encoding, pre-retrieval, at retrieval*). To demonstrate the plausibility of our classes we presented a grounding of each in current XR and memory research. The results of this paper allowed us to classify a new type of perceptual manipulation that has long-term impact on users. We present a discussion about the benefits and risks of this type of perceptual manipulation, taking us a step closer to augmenting the human intellect - but at the cost of jeopardizing perceptual integrity.

## ACKNOWLEDGMENTS

This work was partly supported by French government funding managed by the National Research Agency under the Investments for the Future program (PIA) grant ANR-21-ESRE-0030 (CONTINUUM). We thank all the workshop participants for their contribution, as well as the anonymous reviewers for their valuable feedbacks.

## REFERENCES

- [1] Mahdi Nasrullah Al-Ameen, Matthew Wright, and Shannon Scielzo. 2015. Towards Making Random Passwords Memorable: Leveraging Users' Cognitive Ability Through Multiple Cues. In *Proceedings of the 33rd Annual ACM Conference on Human Factors in Computing Systems (CHI '15)*. Association for Computing Machinery, New York, NY, USA, 2315–2324. <https://doi.org/10.1145/2702123.2702241>
- [2] Cristina Alberini. 2011. The Role of Reconsolidation and the Dynamic Process of Long-Term Memory Formation and Storage. *Frontiers in Behavioral Neuroscience* 5 (2011).
- [3] Cristina M. Alberini and Joseph E. LeDoux. 2013. Memory Reconsolidation. *Current Biology* 23, 17 (Sept. 2013), R746–R750. <https://doi.org/10.1016/j.cub.2013.06.046>
- [4] Nadisha-Marie Aliman and Leon Kester. 2020. Malicious Design in AIVR, Falsehood and Cybersecurity-oriented Immersive Defenses. In *2020 IEEE International Conference on Artificial Intelligence and Virtual Reality (AIVR)*. 130–137. <https://doi.org/10.1109/AIVR50618.2020.00031>
- [5] Mahdi Azmandian, Mark Hancock, Hrvoje Benko, Eyal Ofek, and Andrew D. Wilson. 2016. Haptic Retargeting: Dynamic Repurposing of Passive Haptics for Enhanced Virtual Reality Experiences. In *Proceedings of the 2016 Chi Conference on Human Factors in Computing Systems*. 1968–1979.
- [6] Alan Baddeley, Vivien Lewis, Margery Eldridge, and Neil Thomson. 1984. Attention and Retrieval from Long-Term Memory. *Journal of Experimental Psychology: General* 113 (1984), 518–540. <https://doi.org/10.1037/0096-3445.113.4.518>
- [7] Harry P. Bahrick. 2000. Long-Term Maintenance of Knowledge. (2000).
- [8] Stefano Baldassi, Tadayoshi Kohno, Franziska Roesner, and Moqian Tian. 2018. Challenges and New Directions in Augmented Reality, Computer Security, and Neuroscience—Part 1: Risks to Sensation and Perception. *arXiv preprint arXiv:1806.10557* (2018). [arXiv:1806.10557](https://arxiv.org/abs/1806.10557)
- [9] Emma Berry, Narinder Kapur, Lyndsay Williams, Steve Hodges, Peter Watson, Gavin Smyth, James Srinivasan, Reg Smith, Barbara Wilson, and Ken Wood. 2007 Aug-Oct. The Use of a Wearable Camera, SenseCam, as a Pictorial Diary to Improve Autobiographical Memory in a Patient with Limbic Encephalitis: A Preliminary Report. *Neuropsychological Rehabilitation* 17, 4-5 (2007 Aug-Oct), 582–601. <https://doi.org/10.1080/09602010601029780>
- [10] Agon Bexheti, Marc Langheinrich, Ivan Elhart, and Nigel Davies. 2019. Securely Storing and Sharing Memory Cues in Memory Augmentation Systems: A Practical Approach. In *2019 IEEE International Conference on Pervasive Computing and Communications (PerCom)*. 1–10. <https://doi.org/10.1109/PERCOM.2019.8767389>
- [11] Mark Billinghurst, Adrian Clark, and Gun Lee. 2015. A Survey of Augmented Reality. *Foundations and Trends® in Human-Computer Interaction* 8, 2-3 (March 2015), 73–272. <https://doi.org/10.1561/11000000049>
- [12] Olaf Blanke, Lucie Bréchet, Robin Mange, Bruno Herbelin, Baptiste Gauthier, and Andrea Serino. 2018. *Viewing One's Body during Encoding Boosts Episodic Memory*. <https://doi.org/10.1101/318956>
- [13] Philippe Blondé, Jean-Charles Girardeau, Marco Sperduti, and Pascale Piolino. 2022. A Wandering Mind Is a Forgetful Mind: A Systematic Review on the Influence of Mind Wandering on Episodic Memory Encoding. *Neuroscience & Biobehavioral Reviews* 132 (Jan. 2022), 774–792. <https://doi.org/10.1016/j.neubiorev.2021.11.015>
- [14] Susan Bluck, Nicole Alea, Tilmann Habermas, and David C. Rubin. 2005. A TALE of Three Functions: The Self-Reported Uses of Autobiographical Memory. *Social Cognition* 23, 1 (Feb. 2005), 91–117. <https://doi.org/10.1521/soco.23.1.91.59198>
- [15] Joseph Bonneau and Stuart Schechter. 2014. Towards Reliable Storage of 56-Bit Secrets in Human Memory. In *23rd USENIX Security Symposium (USENIX Security 14)*. 607–623.
- [16] Fred B. Bryant, Colette M. Smart, and Scott P. King. 2005. Using the Past to Enhance the Present: Boosting Happiness Through Positive Reminiscence. *Journal of Happiness Studies* 6, 3 (Sept. 2005), 227–260. <https://doi.org/10.1007/s10902-005-3889-4>
- [17] Larry Cahill and James L. McGaugh. 1998. Mechanisms of Emotional Arousal and Lasting Declarative Memory. *Trends in Neurosciences* 21, 7 (July 1998), 294–299. [https://doi.org/10.1016/S0166-2236\(97\)01214-9](https://doi.org/10.1016/S0166-2236(97)01214-9)
- [18] Niamh Caprani, John Greaney, and Nicola Porter. 2006. A Review of Memory Aid Devices for an Ageing Population. *PsychNology Journal* 4, 3 (2006), 205–243.
- [19] Peter Casey, Ibrahim Baggili, and Ananya Yarramreddy. 2021. Immersive Virtual Reality Attacks and the Human Joystick. *IEEE Transactions on Dependable and Secure Computing* 18, 2 (March 2021), 550–562. <https://doi.org/10.1109/TDSC.2019.2907942>
- [20] Claude Castelluccia, Markus Duermuth, Maximilian Golla, and Fatma Deniz. 2017. Towards Implicit Visual Memory-Based Authentication. In *Proceedings 2017 Network and Distributed System Security Symposium*. Internet Society, San Diego, CA. <https://doi.org/10.14722/ndss.2017.23292>
- [21] Neil Charness, Ryan Best, and Dustin Souders. 2012. Memory Function and Supportive Technology. *Gerontechnology : international journal on the fundamental aspects of technology to serve the ageing society* 11, 1 (2012), 10.4017/gt.2012.11.01.006.00. <https://doi.org/10.4017/gt.2012.11.01.006.00>

- [22] Kaiming Cheng, Jeffery F Tian, Tadayoshi Kohno, and Franziska Roesner. 2023. Exploring User Reactions and Mental Models Towards Perceptual Manipulation Attacks in Mixed Reality. *USENIX Security 2023* (2023), 18.
- [23] Lung-Pan Cheng, Eyal Ofek, Christian Holz, Hrvoje Benko, and Andrew D. Wilson. 2017. Sparse Haptic Proxy: Touch Feedback in Virtual Environments Using a General Passive Prop. In *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems (CHI '17)*. Association for Computing Machinery, New York, NY, USA, 3718–3728. <https://doi.org/10.1145/3025453.3025753>
- [24] Yi Fei Cheng, Hang Yin, Yukang Yan, Jan Gugenheimer, and David Lindlbauer. 2022. Towards Understanding Diminished Reality. In *Proceedings of the 2022 CHI Conference on Human Factors in Computing Systems (CHI '22)*. Association for Computing Machinery, New York, NY, USA, 1–16. <https://doi.org/10.1145/3491102.3517452>
- [25] Sarah Clinch, Cathleen Cortis Mack, Geoff Ward, and Madeleine Steeds. 2021. Technology-Mediated Memory Impairment. In *Technology-Augmented Perception and Cognition*, Tilman Dingler and Evangelos Niforatos (Eds.). Springer International Publishing, Cham, 71–124. [https://doi.org/10.1007/978-3-030-30457-7\\_4](https://doi.org/10.1007/978-3-030-30457-7_4)
- [26] Dan Cosley, Kathy Akey, Brian Alson, Jonathan Baxter, Mark Broomfield, Soyoung Lee, and Chethan Sarabu. 2009. Using Technologies to Support Reminiscence. In *British Computer Society*. 480–484.
- [27] Nelson Cowan. 1988. Evolving Conceptions of Memory Storage, Selective Attention, and Their Mutual Constraints within the Human Information-Processing System. *Psychological bulletin* 104, 2 (1988), 163.
- [28] Fergus I. M. Craik, Richard Govoni, Moshe Naveh-Benjamin, and Nicole D. Anderson. 1996. The Effects of Divided Attention on Encoding and Retrieval Processes in Human Memory. *Journal of Experimental Psychology: General* 125 (1996), 159–180. <https://doi.org/10.1037/0096-3445.125.2.159>
- [29] Anne A. Cuperus and Ineke J. M. van der Ham. 2016. Virtual Reality Replays of Sports Performance: Effects on Memory, Feeling of Competence, and Performance. *Learning and Motivation* 56 (Nov. 2016), 48–52. <https://doi.org/10.1016/j.lmot.2016.09.005>
- [30] Sauvik Das, David Lu, Taehoon Lee, Joanne Lo, and Jason I. Hong. 2019. The Memory Palace: Exploring Visual-Spatial Paths for Strong, Memorable, Infrequent Authentication. In *Proceedings of the 32nd Annual ACM Symposium on User Interface Software and Technology (UIST '19)*. Association for Computing Machinery, New York, NY, USA, 1109–1121. <https://doi.org/10.1145/3332165.3347917>
- [31] Nigel Davies, Adrian Friday, Sarah Clinch, Corina Sas, Marc Langheinrich, Geoff Ward, and Albrecht Schmidt. 2015. Security and Privacy Implications of Pervasive Memory Augmentation. *IEEE Pervasive Computing* 14 (Jan. 2015), 44–53. <https://doi.org/10.1109/MPRV.2015.13>
- [32] Robert Desimone and John Duncan. 1995. Neural Mechanisms of Selective Visual Attention. *Annual review of neuroscience* 18, 1 (1995), 193–222.
- [33] JoAnn Difede and Judith Cukor. 2007. Virtual Reality Exposure Therapy for the Treatment of Posttraumatic Stress Disorder Following September 11, 2001. *The Journal of Clinical Psychiatry* 68, 11 (Nov. 2007), 1682–1689. <https://doi.org/10.4088/JCP.v68n1102>
- [34] H.Q. Dinh, N. Walker, L.F. Hodges, Chang Song, and A. Kobayashi. 1999. Evaluating the Importance of Multi-Sensory Input on Memory and the Sense of Presence in Virtual Environments. In *Proceedings IEEE Virtual Reality (Cat. No. 99CB36316)*. 222–228. <https://doi.org/10.1109/VR.1999.756955>
- [35] Jayesh Doolani, Matthew Wright, Rajesh Setty, and S M Taibul Haque. 2021. LociMotion: Towards Learning a Strong Authentication Secret in a Single Session. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems (CHI '21)*. Association for Computing Machinery, New York, NY, USA, 1–13. <https://doi.org/10.1145/3411764.3445105>
- [36] John V. Draper, David B. Kaber, and John M. Usher. 1998. Telepresence. *Human Factors* 40, 3 (Sept. 1998), 354–375. <https://doi.org/10.1518/001872098779591386>
- [37] Hermann Ebbinghaus (1885). 1885. Memory: A Contribution to Experimental Psychology. *Annals of Neurosciences* 20, 4 (1885), 155–156. <https://doi.org/10.5214/ans.0972.7531.200408>
- [38] Emmaline Drew Eliseev and Elizabeth J. Marsh. 2021. Externalizing Autobiographical Memories in the Digital Age. *Trends in Cognitive Sciences* 25, 12 (Dec. 2021), 1072–1081. <https://doi.org/10.1016/j.tics.2021.08.005>
- [39] Douglas C Engelbart. 1962. Augmenting human intellect: A conceptual framework. *Menlo Park, CA* (1962), 21.
- [40] Michael W. Eysenck and Mark T. Keane. 2020. *Cognitive Psychology: A Student's Handbook*. Psychology Press.
- [41] Anna Felnhöfer, Oswald D. Kothgassner, Mareike Schmidt, Anna-Katharina Heinze, Leon Beutl, Helmut Hlavacs, and Ilse Kryspin-Exner. 2015. Is Virtual Reality Emotionally Arousing? Investigating Five Emotion Inducing Virtual Park Scenarios. *International Journal of Human-Computer Studies* 82 (Oct. 2015), 48–56. <https://doi.org/10.1016/j.ijhcs.2015.05.004>
- [42] Andreas Rene Fender and Christian Holz. 2022. Causality-Preserving Asynchronous Reality. In *Proceedings of the 2022 CHI Conference on Human Factors in Computing Systems (CHI '22)*. Association for Computing Machinery, New York, NY, USA, 1–15. <https://doi.org/10.1145/3491102.3501836>
- [43] Ajoy S. Fernandes, Ranxiao Frances Wang, and Daniel J. Simons. 2015. Remembering the Physical as Virtual: Source Confusion and Physical Interaction in Augmented Reality. In *Proceedings of the ACM SIGGRAPH Symposium on Applied Perception (SAP '15)*. Association for Computing Machinery, New York, NY, USA, 127–130. <https://doi.org/10.1145/2804408.2804423>
- [44] The Neurorights Foundation. 2021. *Mission*. Retrieved January 25, 2023 from <https://neurorightsfoundation.org/mission>
- [45] Doron Friedman, Rodrigo Pizarro, Keren Or-Berkers, Solène Neyret, Xueni Pan, and Mel Slater. 2014. A Method for Generating an Illusion of Backwards Time Travel Using Immersive Virtual Reality—an Exploratory Study. *Frontiers in psychology* 5 (2014), 943.
- [46] Maryrose Gerardi, Barbara Olasov Rothbaum, Kerry Ressler, Mary Heekin, and Albert Rizzo. 2008. Virtual reality exposure therapy using a virtual Iraq: Case report. *Journal of Traumatic Stress* 21, 2 (2008), 209–213. <https://doi.org/10.1002/jts.20331>
- [47] Mar Gonzalez-Franco and Jaron Lanier. 2017. Model of Illusions and Virtual Reality. *Frontiers in Psychology* 8 (2017), 1125. <https://doi.org/10.3389/fpsyg.2017.01125>
- [48] Jan Gugenheimer. 2016. Nomadic Virtual Reality: Exploring New Interaction Concepts for Mobile Virtual Reality Head-Mounted Displays. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology*. 9–12.
- [49] Jan Gugenheimer, Christian Mai, Mark McGill, Julie Williamson, Frank Steinicke, and Ken Perlin. 2019. Challenges Using Head-Mounted Displays in Shared and Social Spaces. In *Extended Abstracts of the 2019 CHI Conference on Human Factors in Computing Systems*. 1–8.
- [50] Jan Gugenheimer, Mark McGill, Samuel Huron, Christian Mai, Julie Williamson, and Michael Nebeling. 2020. Exploring Potentially Abusive Ethical, Social and Political Implications of Mixed Reality Research in HCI. In *Extended Abstracts of the 2020 CHI Conference on Human Factors in Computing Systems (CHI EA '20)*. Association for Computing Machinery, New York, NY, USA, 1–8. <https://doi.org/10.1145/3334480.3375180>
- [51] Cathal Gurrin, Alan F. Smeaton, and Aiden R. Doherty. 2014. LifeLogging: Personal Big Data. *Foundations and Trends® in Information Retrieval* 8, 1 (June 2014), 1–125. <https://doi.org/10.1561/15000000033>
- [52] Morgan Harvey, Marc Langheinrich, and Geoff Ward. 2016. Remembering through Lifelogging: A Survey of Human Memory Augmentation. *Pervasive and Mobile Computing* 27 (April 2016), 14–26. <https://doi.org/10.1016/j.pmcj.2015.12.002>
- [53] Linda A. Henkel. 2014. Point-and-Shoot Memories: The Influence of Taking Photos on Memory for a Museum Tour. *Psychological Science* 25, 2 (Feb. 2014), 396–402. <https://doi.org/10.1177/0956797613504438>
- [54] Jan Herling and Wolfgang Broll. 2012. Pixmix: A Real-Time Approach to High-Quality Diminished Reality. In *2012 IEEE International Symposium on Mixed and Augmented Reality (ISMAR)*. IEEE, 141–150.
- [55] H.G. Hoffman, K.C. Hullfish, and S.J. Houston. 1995. Virtual-Reality Monitoring. In *Proceedings Virtual Reality Annual International Symposium '95*. 48–54. <https://doi.org/10.1109/VRAIS.1995.512479>
- [56] Hunter G. Hoffman, Azucena Garcia-Palacios, Ayanna K. Thomas, and Anne Schmidt. 2001. Virtual Reality Monitoring: Phenomenal Characteristics of Real, Virtual, and False Memories. *CyberPsychology & Behavior* 4, 5 (Oct. 2001), 565–572. <https://doi.org/10.1089/109493101753235151>
- [57] Ellen Isaacs, Artie Konrad, Alan Walendowski, Thomas Lennig, Victoria Hollis, and Steve Whittaker. 2013. Echoes from the Past: How Technology Mediated Reflection Improves Well-Being. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems*. 1071–1080.
- [58] Matthew Jamieson, Breda Cullen, Marilyn McGee-Lennon, Stephen Brewster, and Jonathan J. Evans. 2014. The Efficacy of Cognitive Prosthetic Technology for People with Memory Impairments: A Systematic Review and Meta-Analysis. *Neuropsychological Rehabilitation* 24, 3-4 (July 2014), 419–444. <https://doi.org/10.1080/09602011.2013.825632>
- [59] Matthew Jamieson, Brian O'Neill, Breda Cullen, Marilyn Lennon, Stephen Brewster, and Jonathan Evans. 2017. ForgetMeNot: Active Reminder Entry Support for Adults with Acquired Brain Injury. In *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems (CHI '17)*. Association for Computing Machinery, New York, NY, USA, 6012–6023. <https://doi.org/10.1145/3025453.3025888>
- [60] Marcia K. Johnson, Shahin Hashtroudi, and D. Stephen Lindsay. 1993. Source Monitoring. *Psychological Bulletin* 114, 1 (1993), 3–28. <https://doi.org/10.1037/0033-2909.114.1.3>
- [61] Marcia K. Johnson and Carol L. Raye. 1981. Reality Monitoring. *Psychological Review* 88, 1 (1981), 67–85. <https://doi.org/10.1037/0033-295X.88.1.67>
- [62] Zeinab Joudaki, Julie Thorpe, and Miguel Vargas Martin. 2018. Reinforcing System-Assigned Passphrases Through Implicit Learning. In *Proceedings of the 2018 ACM SIGSAC Conference on Computer and Communications Security (CCS '18)*. Association for Computing Machinery, New York, NY, USA, 1533–1548. <https://doi.org/10.1145/3243734.3243764>

- [63] Joanna Kisker, Thomas Gruber, and Benjamin Schöne. 2021. Virtual Reality Experiences Promote Autobiographical Retrieval Mechanisms: Electrophysiological Correlates of Laboratory and Virtual Experiences. *Psychological Research* 85, 7 (Oct. 2021), 2485–2501. <https://doi.org/10.1007/s00426-020-01417-x>
- [64] Cadu Klier and Luciano Grütner Buratto. 2020. Stress and Long-Term Memory Retrieval: A Systematic Review. *Trends in Psychiatry and Psychotherapy* 42, 3 (2020), 284–291. <https://doi.org/10.1590/2237-6089-2019-0077>
- [65] Artie Konrad, Ellen Isaacs, and Steve Whittaker. 2016. Technology-Mediated Memory: Is Technology Altering Our Memories And Interfering With Well-Being? *ACM Transactions on Computer-Human Interaction* 23, 4 (Aug. 2016), 23:1–23:29. <https://doi.org/10.1145/2934667>
- [66] Artie Konrad, Simon Tucker, John Crane, and Steve Whittaker. 2016. Technology and Reflection: Mood and Memory Mechanisms for Well-Being. *Psychology of Well-Being* 6 (2016), 5. <https://doi.org/10.1186/s13612-016-0045-3>
- [67] Michael Kotlyar, Christopher Donahue, Paul Thuras, Matt G. Kushner, Natalie O’Gorman, Erin A Smith, and David E. Adson. 2008. Physiological Response to a Speech Stressor Presented in a Virtual Reality Environment. *Psychophysiology* 45, 6 (2008), 1034–1037. <https://doi.org/10.1111/j.1469-8986.2008.00690.x>
- [68] Eric Krokos, Catherine Plaisant, and Amitabh Varshney. 2019. Virtual Memory Palaces: Immersion Aids Recall. *Virtual Reality* 23, 1 (March 2019), 1–15. <https://doi.org/10.1007/s10055-018-0346-3>
- [69] Kiron Lebeck, Tadayoshi Kohno, and Franziska Roesner. 2016. How to Safely Augment Reality: Challenges and Directions. In *Proceedings of the 17th International Workshop on Mobile Computing Systems and Applications*. 45–50.
- [70] Kiron Lebeck, Kimberly Ruth, Tadayoshi Kohno, and Franziska Roesner. 2017. Securing Augmented Reality Output. In *2017 IEEE Symposium on Security and Privacy (SP)*. IEEE, 320–337.
- [71] Eric L. G. Legge, Christopher R. Madan, Enoch T. Ng, and Jeremy B. Caplan. 2012. Building a Memory Palace in Minutes: Equivalent Memory Performance Using Virtual versus Conventional Environments with the Method of Loci. *Acta Psychologica* 141, 3 (Nov. 2012), 380–390. <https://doi.org/10.1016/j.actpsy.2012.09.002>
- [72] Eric L. G. Legge, Christopher R. Madan, Enoch T. Ng, and Jeremy B. Caplan. 2012. Building a Memory Palace in Minutes: Equivalent Memory Performance Using Virtual versus Conventional Environments with the Method of Loci. *Acta Psychologica* 141, 3 (Nov. 2012), 380–390. <https://doi.org/10.1016/j.actpsy.2012.09.002>
- [73] Diane Lenormand and Pascale Piolino. 2022. In Search of a Naturalistic Neuroimaging Approach: Exploration of General Feasibility through the Case of VR-fMRI and Application in the Domain of Episodic Memory. *Neuroscience & Biobehavioral Reviews* 133 (Feb. 2022), 104499. <https://doi.org/10.1016/j.neubiorev.2021.12.022>
- [74] David Lindlbauer and Andy D. Wilson. 2018. Remixed Reality: Manipulating Space and Time in Augmented Reality. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems (CHI '18)*. Association for Computing Machinery, New York, NY, USA, 1–13. <https://doi.org/10.1145/3173574.3173703>
- [75] Elizabeth F. Loftus. 2005. Planting Misinformation in the Human Mind: A 30-Year Investigation of the Malleability of Memory. *Learning & Memory* 12, 4 (Jan. 2005), 361–366. <https://doi.org/10.1101/lm.94705>
- [76] Elizabeth F. Loftus and Jacqueline E. Pickrell. 1995. The Formation of False Memories. *Psychiatric Annals* 25, 12 (Dec. 1995), 720–725. <https://doi.org/10.3928/0048-5713-19951201-07>
- [77] Dominique Makowski, Marco Sperduti, Serge Nicolas, and Pascale Piolino. 2017. “Being There” and Remembering It: Presence Improves Memory Encoding. *Consciousness and Cognition* 53 (2017), 194–202.
- [78] Marieke AG Martens, Angus Antley, Daniel Freeman, Mel Slater, Paul J Harrison, and Elizabeth M Tunbridge. 2019. It Feels Real: Physiological Responses to a Stressful Virtual Reality Environment and Its Impact on Working Memory. *Journal of Psychopharmacology* 33, 10 (Oct. 2019), 1264–1273. <https://doi.org/10.1177/0269881119860156>
- [79] Sebastian Marwecki, Andrew D. Wilson, Eyal Ofek, Mar Gonzalez Franco, and Christian Holz. 2019. Mise-Unseen: Using Eye Tracking to Hide Virtual Reality Scene Changes in Plain Sight. In *Proceedings of the 32nd Annual ACM Symposium on User Interface Software and Technology (UIST '19)*. Association for Computing Machinery, New York, NY, USA, 777–789. <https://doi.org/10.1145/3332165.3347919>
- [80] A. McDonald, C. Haslam, P. Yates, B. Gurr, G. Leeder, and A. Sayers. 2011. Google Calendar: A New Memory Aid to Compensate for Prospective Memory Deficits Following Acquired Brain Injury. *Neuropsychological Rehabilitation* 21, 6 (Dec. 2011), 784–807. <https://doi.org/10.1080/09602011.2011.598405>
- [81] James L McGaugh and Benno Roozendaal. 2002. Role of Adrenal Stress Hormones in Forming Lasting Memories in the Brain. *Current Opinion in Neurobiology* 12, 2 (April 2002), 205–210. [https://doi.org/10.1016/S0959-4388\(02\)00306-9](https://doi.org/10.1016/S0959-4388(02)00306-9)
- [82] Arthur W. Melton. 1963. Implications of Short-Term Memory for a General Theory of Memory. *Journal of Verbal Learning and Verbal Behavior* 2, 1 (July 1963), 1–21. [https://doi.org/10.1016/S0022-5371\(63\)80063-8](https://doi.org/10.1016/S0022-5371(63)80063-8)
- [83] Abraham Hani Mhaidli and Florian Schaub. 2021. Identifying Manipulative Advertising Techniques in XR Through Scenario Construction. In *Proceedings of the 2021 CHI Conference on Human Factors in Computing Systems (CHI '21)*. Association for Computing Machinery, New York, NY, USA, 1–18. <https://doi.org/10.1145/3411764.3445253>
- [84] Paul Milgram and Fumio Kishino. 1994. A Taxonomy of Mixed Reality Visual Displays. *IEICE Trans. Information Systems* vol. E77-D, no. 12 (Dec. 1994), 1321–1329.
- [85] Shohei Mori, Sei Ikeda, and Hideo Saito. 2017. A Survey of Diminished Reality: Techniques for Visually Concealing, Eliminating, and Seeing through Real Objects. *IPSJ Transactions on Computer Vision and Applications* 9, 1 (June 2017), 17. <https://doi.org/10.1186/s41074-017-0028-1>
- [86] Robert A. Nash, Kimberley A. Wade, and D. Stephen Lindsay. 2009. Digitally Manipulating Memory: Effects of Doctored Videos and Imagination in Distorting Beliefs and Memories. *Memory & Cognition* 37, 4 (June 2009), 414–424. <https://doi.org/10.3758/MC.37.4.414>
- [87] BBC World News. 2020. *Click, Virtual Time Machine: Watching My Life from 2019*. Retrieved January 25, 2023 from <https://www.bbc.co.uk/programmes/p08nkwk4>
- [88] Alasdair Newson, Andrés Almansa, Matthieu Fradet, Yann Gousseau, and Patrick Pérez. 2013. Towards Fast, Generic Video Inpainting. In *Proceedings of the 10th European Conference on Visual Media Production (CVMP '13)*. Association for Computing Machinery, New York, NY, USA, 1–8. <https://doi.org/10.1145/2534008.2534019>
- [89] OpenAI. 2022. *DALL-E 2*. Retrieved January 25, 2023 from <https://openai.com/dall-e-2/>
- [90] Sylvain Penuad, Najate Jebara, Mohamed Zaoui, Eric Orriols, Alain Berthoz, and Pascale Piolino. 2022. Episodic Memory and Self-Reference in a Naturalistic Context: New Insights Based on a Virtual Walk in the Latin Quarter of Paris. *Journal of Environmental Psychology* 81 (2022), 101801.
- [91] James W. Pennebaker and Sandra K. Beall. 1986. Confronting a Traumatic Event: Toward an Understanding of Inhibition and Disease. *Journal of abnormal psychology* 95, 3 (1986), 274.
- [92] PetaPixel. 2018. *Facebook Can Reconstruct a 3D World from Your Photos and Videos*. Retrieved January 25, 2023 from <https://petapixel.com/2018/05/02/facebook-can-reconstruct-a-3d-world-from-your-photos-and-videos/>
- [93] Elizabeth A Phelps. 2004. Human Emotion and Memory: Interactions of the Amygdala and Hippocampal Complex. *Current Opinion in Neurobiology* 14, 2 (April 2004), 198–202. <https://doi.org/10.1016/j.conb.2004.03.015>
- [94] Laurence Picard, Maria Abram, Eric Orriols, and Pascale Piolino. 2017. Virtual Reality as an Ecologically Valid Tool for Assessing Multifaceted Episodic Memory in Children and Adolescents. *International Journal of Behavioral Development* 41, 2 (March 2017), 211–219. <https://doi.org/10.1177/0165025415616198>
- [95] Michael I. Posner, Mary J. Nissen, and Raymond M. Klein. 1976. Visual Dominance: An Information-Processing Account of Its Origins and Significance. *Psychological review* 83, 2 (1976), 157.
- [96] Zhen Qin, Qingliang Zeng, Yixin Zong, and Fan Xu. 2021. Image Inpainting Based on Deep Learning: A Review. *Displays* 69 (Sept. 2021), 102028. <https://doi.org/10.1016/j.displa.2021.102028>
- [97] Sharif Razzaque, David Swapp, Mel Slater, Mary Whitton, and Anthony Steed. 2002. Redirected Walking in Place. *Eight Eurographics Workshop on Virtual Environments* (Jan. 2002).
- [98] E. F. Risko, M. O. Kelly, P. Patel, and C. Gaspar. 2019. Offloading Memory Leaves Us Vulnerable to Memory Manipulation. *Cognition* 191 (Oct. 2019), 103954. <https://doi.org/10.1016/j.cognition.2019.04.023>
- [99] Franziska Roesner and Tadayoshi Kohno. 2021. Security and Privacy for Augmented Reality: Our 10-Year Retrospective. In *VR4Sec: 1st International Workshop on Security for XR and XR for Security*.
- [100] Franziska Roesner, Tadayoshi Kohno, and David Molnar. 2014. Security and Privacy for Augmented Reality Systems. *Commun. ACM* 57, 4 (2014), 88–96.
- [101] Oscar Rosello, Marc Exposito, and Pattie Maes. 2016. NeverMind: Using Augmented Reality for Memorization. In *Proceedings of the 29th Annual Symposium on User Interface Software and Technology (UIST '16 Adjunct)*. Association for Computing Machinery, New York, NY, USA, 215–216. <https://doi.org/10.1145/2984751.2984776>
- [102] Marius Rubo, Nadine Messerli, and Simone Munsch. 2021. The Human Source Memory System Struggles to Distinguish Virtual Reality and Reality. *Computers in Human Behavior Reports* 4 (Aug. 2021), 100111. <https://doi.org/10.1016/j.chbr.2021.100111>
- [103] Maria V. Sanchez-Vives and Mel Slater. 2005. From Presence to Consciousness through Virtual Reality. *Nature Reviews Neuroscience* 6, 4 (April 2005), 332–339. <https://doi.org/10.1038/nrn1651>
- [104] Susan J. Sara. 2000. Retrieval and Reconsolidation: Toward a Neurobiology of Remembering. *Learning & Memory* 7, 2 (Jan. 2000), 73–84. <https://doi.org/10.1101/lm.7.2.73>
- [105] Corina Sas and Steve Whittaker. 2013. Design for Forgetting: Disposing of Digital Possessions after a Breakup. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '13)*. Association for Computing Machinery, New York, NY, USA, 1823–1832. <https://doi.org/10.1145/2470654.2466241>
- [106] Daniel L. Schacter. 2002. *The Seven Sins of Memory: How the Mind Forgets and Remembers*. HMH.

- [107] Daniel L. Schacter. 2022. Media, Technology, and the Sins of Memory. *Memory, Mind & Media* 1 (2022), e1. <https://doi.org/10.1017/mem.2021.3>
- [108] Daniel L. Schacter and Chad S. Dodson. 2001. Misattribution, False Recognition and the Sins of Memory. *Philosophical Transactions of the Royal Society of London. Series B: Biological Sciences* 356, 1413 (Sept. 2001), 1385–1393. <https://doi.org/10.1098/rstb.2001.0938>
- [109] Kathryn Y. Segovia and Jeremy N. Bailenson. 2009. Virtually True: Children's Acquisition of False Memories in Virtual Reality. *Media Psychology* 12, 4 (Nov. 2009), 371–393. <https://doi.org/10.1080/15213260903287267>
- [110] Abigail J. Sellen, Andrew Fogg, Mike Aitken, Steve Hodges, Carsten Rother, and Ken Wood. 2007. Do Life-Logging Technologies Support Memory for the Past? An Experimental Study Using Sensecam. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '07)*. Association for Computing Machinery, New York, NY, USA, 81–90. <https://doi.org/10.1145/1240624.1240636>
- [111] Andrew M. Sherrill, Alex O. Rothbaum, Lauren B. McSweeney, and Barbara O. Rothbaum. 2019. Virtual Reality Exposure Therapy for Posttraumatic Stress Disorder. *Psychiatric Annals* 49, 8 (Aug. 2019), 343–347. <https://doi.org/10.3928/00485713-20190716-02>
- [112] R. M. Shiffrin and R. C. Atkinson. 1969. Storage and Retrieval Processes in Long-Term Memory. *Psychological Review* 76 (1969), 179–193. <https://doi.org/10.1037/h0027277>
- [113] Youngsoo Shin, Ruth Barankevich, Jina Lee, and Saleh Kalantari. 2021. PEN-CODER: Design for Prospective Memory and Older Adults. In *Extended Abstracts of the 2021 CHI Conference on Human Factors in Computing Systems (CHI EA '21)*. Association for Computing Machinery, New York, NY, USA, 1–7. <https://doi.org/10.1145/3411763.3451795>
- [114] Panote Siriarraya and Chee Siang Ang. 2014. Recreating Living Experiences from Past Memories through Virtual Worlds for People with Dementia. In *Proceedings of the SIGCHI Conference on Human Factors in Computing Systems (CHI '14)*. Association for Computing Machinery, New York, NY, USA, 3977–3986. <https://doi.org/10.1145/2556288.2557035>
- [115] Mel Slater. 2009. Place Illusion and Plausibility Can Lead to Realistic Behaviour in Immersive Virtual Environments. *Philosophical Transactions of the Royal Society B: Biological Sciences* 364, 1535 (2009), 3549–3557.
- [116] Mel Slater, Cristina Gonzalez-Lieners, Patrick Haggard, Charlotte Vinkers, Rebecca Gregory-Clarke, Steve Jelley, Zillah Watson, Graham Breen, Raz Schwarz, William Steptoe, et al. 2020. The Ethics of Realism in Virtual and Augmented Reality. *Frontiers in Virtual Reality* 1 (2020), 1.
- [117] Mel Slater and Sylvia Wilbur. 1997. A Framework for Immersive Virtual Environments (FIVE): Speculations on the Role of Presence in Virtual Environments. *Presence: Teleoperators & Virtual Environments* 6, 6 (1997), 603–616.
- [118] S. Adam Smith. 2019. Virtual Reality in Episodic Memory Research: A Review. *Psychonomic Bulletin & Review* 26, 4 (Aug. 2019), 1213–1237. <https://doi.org/10.3758/s13423-019-01605-w>
- [119] Bernhard Spanlang, Jean-Marie Normand, David Borland, Konstantina Kilteni, Elias Giannopoulos, Ausiàs Pomés, Mar González-Franco, Daniel Perez-Marcos, Jorge Arroyo-Palacios, Xavi Navarro Muncunill, and Mel Slater. 2014. How to Build an Embodiment Lab: Achieving Body Representation Illusions in Virtual Reality. *Frontiers in Robotics and AI* 1 (2014).
- [120] Jonathan D Spence. 1984. *The Memory Palace of Matteo Ricci*. Viking.
- [121] Stability.AI. 2022. *Stable Diffusion 2.0 Release*. Retrieved January 25, 2023 from <https://stability.ai/blog/stable-diffusion-v2-release>
- [122] Frank Steinicke, Gerd Bruder, Jason Jerald, Harald Frenz, and Markus Lappe. 2010. Estimation of Detection Thresholds for Redirected Walking Techniques. *IEEE Transactions on Visualization and Computer Graphics* 16, 1 (Jan. 2010), 17–27. <https://doi.org/10.1109/TVCG.2009.62>
- [123] Qi Sun, Anjul Patney, Li-Yi Wei, Omer Shapira, Jingwan Lu, Paul Asente, Suwen Zhu, Morgan Mcguire, David Luebke, and Arie Kaufman. 2018. Towards Virtual Reality Infinite Walking: Dynamic Saccadic Redirection. *ACM Transactions on Graphics* 37, 4 (July 2018), 67:1–67:13. <https://doi.org/10.1145/3197517.3201294>
- [124] Charles P. Thompson, John J. Skowronski, Steen F. Larsen, and Andrew L. Betz. 2013. *Autobiographical Memory: Remembering What and Remembering When*. Psychology Press.
- [125] Yung-Chin Tsao, Chun-Chieh Shu, and Tian-Syung Lan. 2019. Development of a Reminiscence Therapy System for the Elderly Using the Integration of Virtual Reality and Augmented Reality. *Sustainability* 11, 17 (Jan. 2019), 4792. <https://doi.org/10.3390/su11174792>
- [126] Wen-jie Tseng, Elise Bonnail, Mark McGill, Mohamed Khamis, Eric Lecolinet, Samuel Huron, and Jan Gugenheimer. 2022. The Dark Side of Perceptual Manipulations in Virtual Reality. *arXiv:2202.13200 [cs]* (Feb. 2022). <https://doi.org/10.1145/3491102.3517728> [arXiv:2202.13200 \[cs\]](https://arxiv.org/abs/2202.13200)
- [127] Chai M. Tynng, Hafeez U. Amin, Mohamad N. M. Saad, and Aamir S. Malik. 2017. The Influences of Emotion on Learning and Memory. *Frontiers in Psychology* 8 (Aug. 2017), 1454. <https://doi.org/10.3389/fpsyg.2017.01454>
- [128] Eunjoon “Rachel” Um, Jan L. Plass, Elizabeth O. Hayward, and Bruce D. Homer. 2012. Emotional Design in Multimedia Learning. *Journal of Educational Psychology* 104, 2 (2012), 485–498. <https://doi.org/10.1037/a0026609>
- [129] Melina R. Uncapher and Michael D. Rugg. 2009. Selecting for Memory? The Influence of Selective Attention on the Mnemonic Binding of Contextual Information. *Journal of Neuroscience* 29, 25 (June 2009), 8270–8279. <https://doi.org/10.1523/JNEUROSCI.1043-09.2009>
- [130] Robert J. van Beers, Daniel M. Wolpert, and Patrick Haggard. 2002. When Feeling Is More Important than Seeing in Sensorimotor Adaptation. *Current biology* 12, 10 (2002), 834–837.
- [131] Joakim Vindenes, Angelica Ortiz de Gortari, and Barbara Wasson. 2018. Mnemosyne: Adapting the Method of Loci to Immersive Virtual Reality. In *Augmented Reality, Virtual Reality, and Computer Graphics (Lecture Notes in Computer Science)*, Lucio Tommaso De Paolis and Patrick Bourdot (Eds.). Springer International Publishing, Cham, 205–213. [https://doi.org/10.1007/978-3-319-95270-3\\_16](https://doi.org/10.1007/978-3-319-95270-3_16)
- [132] Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. 2015. Show and Tell: A Neural Image Caption Generator. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*. 3156–3164.
- [133] Susanne Vogel and Lars Schwabe. 2016. Learning and Memory under Stress: Implications for the Classroom. *npj Science of Learning* 1, 1 (June 2016), 1–10. <https://doi.org/10.1038/npjscilearn.2016.11>
- [134] Kimberley A. Wade, Maryanne Garry, J. Don Read, and D. Stephen Lindsay. 2002. A Picture Is Worth a Thousand Lies: Using False Photographs to Create False Childhood Memories. *Psychonomic Bulletin & Review* 9, 3 (Sept. 2002), 597–603. <https://doi.org/10.3758/BF03196318>
- [135] Oliver T Wolf. 2017. Stress and Memory Retrieval: Mechanisms and Consequences. *Current Opinion in Behavioral Sciences* 14 (April 2017), 40–46. <https://doi.org/10.1016/j.cobeha.2016.12.001>
- [136] Bob Woods, Laura O'Philbin, Emma M. Farrell, Aimee E. Spector, and Martin Orrell. 2018. Reminiscence Therapy for Dementia. *Cochrane Database of Systematic Reviews* 3 (2018). <https://doi.org/10.1002/14651858.CD001120.pub3>
- [137] Jiaxin Xu and Baosheng Wang. 2020. Efficacy of VR-Based Reminiscence Therapy in Improving Autobiographical Memory for Chinese Patients with AD. 339–349. [https://doi.org/10.1007/978-3-030-51038-1\\_47](https://doi.org/10.1007/978-3-030-51038-1_47)
- [138] Yuki Yamada, Keisuke Irie, Kota Gushima, Fumiko Ishizawa, Mohammed Al Sada, and Tatsuo Nakajima. 2017. HoloMoL: Human Memory Augmentation with Mixed-Reality Technologies. In *Proceedings of the 21st International Academic Mindtrek Conference (AcademicMindtrek '17)*. Association for Computing Machinery, New York, NY, USA, 235–238. <https://doi.org/10.1145/3131085.3131097>
- [139] Zhong-Qiu Zhao, Peng Zheng, Shou-Tao Xu, and Xindong Wu. 2019. Object Detection With Deep Learning: A Review. *IEEE Transactions on Neural Networks and Learning Systems* 30, 11 (Nov. 2019), 3212–3232. <https://doi.org/10.1109/TNNLS.2018.2876865>
- [140] Patrick Zimmer, Benjamin Buttler, Georg Halbeisen, Eva Walther, and Gregor Domes. 2019. Virtually Stressed? A Refined Virtual Reality Adaptation of the Trier Social Stress Test (TSST) Induces Robust Endocrine Responses. *Psychoneuroendocrinology* 101 (March 2019), 186–192. <https://doi.org/10.1016/j.psyneuen.2018.11.010>

Id	Name	Author	Description	Class
S1	Peak-End Rule	PXR2	Positive emotions are induced during the XR experience, to increase positive memories and overall happiness. This manipulation is implemented by the developers to make users come back to the app.	At encoding Influencing encoding by inducing emotions
S2	You'll Remember the Unlikely Event	PM1	Risky and stressful events are simulated when learning how to drive, so the important lessons are better remembered. This manipulation is a feature of the training app.	
S3	Make Forget	PXR4	An attacker add distractions in other user's AR field of view, to make them less attentive and forget what they just did, to make them vulnerable to other attacks (e.g., stealing money).	At encoding Influencing encoding by steering attention
S4	Attention Detector	PM3	An AR app helps users with Attention Deficit Disorder (ADD) to detect and notify them when they are not attentive, to increase the chance of correctly encoding events.	
S5	Encoding Enhancer	PM4	An AR app helps users in a learning context by blurring distractions and contextual information (sounds, objects, movements...), to help them focus and enhance encoding.	
S6	This You Should Remember	PXR5	An AR app proposes to support encoding, through an AI which selects what users should remember, by highlighting important elements and blurring distractions (fig.5).	At retrieval Influencing perception through reflection
S7	Traumatic Memory	PM2	During a therapy, patients suffering from PTSD are exposed to their trauma in VR, to reduce flashbacks.	
S8	Therapy	PM2	During a therapy, patients are immersed in the context of a past event in VR, to help them analyse the situation and understand the past better.	
S9	Couple Game	PXR3	A VR game allows couples to experience each other memories, to help them understand each other better.	
S10	Dysmorphia	PM3	During a therapy, patients suffering from dysmorphia can revisit their memories in VR to correct their self-perception thanks to embodiment.	
S11	Memory Training	PM4	A VR app proposes to insert users' relatives in VR entertaining content to help users suffering from dementia to remember their relatives.	
S12	Shame Reminder	PXR4	An AR app reminds users' of memories linked to places. This app makes profit by reviving traumatic memories, because users have to pay to stop being reminded of them.	
S13	Naked Man VR	PXR5	An attacker inadvertently exposes VR users to reconstruction of traumatic events, to harm their mental state and make them vulnerable.	
S14	Speech	PM1	A VR speech training app proposes to re-experience previous speech performances, through 3D reconstructions. These reconstructions are positively altered, to enhance user's self-perception.	
S15	Real Estate	PXR1	A real estate company alters VR reconstructions of properties, so that memories of potential buyers who revisit them in VR are distorted and more positive, to influence them to buy them.	
S16	Judge Training	PM1	A judge training VR app proposes to visit reconstructions of previous trials. These reconstructions are altered by changing people's gender and race to help judges reducing bias.	
S17	Parallel Album	PXR3	An attacker alters VR family albums of an old man, to blur their souvenirs and make them vulnerable.	
S18	Buy a Friend	PXR4	A VR social media to share immersive memories allows premium users to be inserted in other users' memories (fig.6).	
S19	Burning Stove	PXR6	An attacker displays previously experienced events in the AR user's field of view, to make them mix memories of the past with the present, and make them vulnerable.	
S20	What's Up Girl	PXR5	VR is used to relieve past experiences. An attacker alters the recordings, to distort people's memories and alter their relationships.	Pre-retrieval Induce forgetting by removing cues
S21	AR Eraser	PXR2	An AR app proposes to help forgetting someone, by hiding all the objects linked to that person (fig.7).	
S22	False Training App	PXR1	In a VR quiz application, users are immersed in a stressful environment to make them forget the answers and feel incompetent, to make they buy a training product.	
S23	College Dropout Spam	PM5	An AR app adds advertisement in the user's field of view in exchange of free education content.	
S24	Smell	PXR6	An XR app to consult products adds smells to trigger emotion and create a comfortable environment, to make users buy their products.	Not considered as XRMM
S25	Stranger Things' Effect	PM5	A VR entertaining app integrates cultural content related to the user's youth (e.g., music), to make people enjoy the content.	

**Table 3: Short description and categorization of the XRMM scenarios generated by participants and discussed during the workshops.**